



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'OSSL_SELF_TEST_set_callback.3oss1' command

`$ man OSSL_SELF_TEST_set_callback.3oss1`

OSSL_SELF_TEST_SET_CALLBACK(3oss1) OpenSSL OSSL_SELF_TEST_SET_CALLBACK(3oss1)

NAME

OSSL_SELF_TEST_set_callback, OSSL_SELF_TEST_get_callback - specify a callback for processing self tests

SYNOPSIS

```
#include <openssl/self_test.h>
```

```
void OSSL_SELF_TEST_set_callback(OSSL_LIB_CTX *ctx, OSSL_CALLBACK *cb, void *cbarg);  
void OSSL_SELF_TEST_get_callback(OSSL_LIB_CTX *ctx, OSSL_CALLBACK **cb, void **cbarg);
```

DESCRIPTION

Set or gets the optional application callback (and the callback argument) that is called during self testing. The application callback OSSL_CALLBACK is associated with a OSSL_LIB_CTX. The application callback function receives information about a running self test, and may return a result to the calling self test. See openssl-core.h(7) for further information on the callback.

RETURN VALUES

OSSL_SELF_TEST_get_callback() returns the callback and callback argument that has been set via OSSL_SELF_TEST_set_callback() for the

given library context ctx. These returned parameters will be NULL if
OSSL_SELF_TEST_set_callback() has not been called.

SEE ALSO

openssl-core.h(7), OSSL_PROVIDER-FIPS(7) OSSL_SELF_TEST_new(3)
OSSL_LIB_CTX(3)

HISTORY

The functions described here were added in OpenSSL 3.0.

COPYRIGHT

Copyright 2019-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use
this file except in compliance with the License. You can obtain a copy
in the file LICENSE in the source distribution or at
<<https://www.openssl.org/source/license.html>>.

3.0.7 2023-07-13 OSSL_SELF_TEST_SET_CALLBACK(3openssl)