



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'OSSL\_parse\_url.3ossl' command**

**\$ man OSSL\_parse\_url.3ossl**

OSSL\_HTTP\_PARSE\_URL(3ossl)      OpenSSL      OSSL\_HTTP\_PARSE\_URL(3ossl)

### NAME

OSSL\_HTTP\_adapt\_proxy, OSSL\_parse\_url, OSSL\_HTTP\_parse\_url,  
OCSP\_parse\_url - http utility functions

### SYNOPSIS

```
#include <openssl/http.h>
```

```
const char *OSSL_HTTP_adapt_proxy(const char *proxy, const char *no_proxy,  
                                const char *server, int use_ssl);
```

```
int OSSL_parse_url(const char *url, char **pscheme, char **puser, char **phost,  
                  char **pport, int *pport_num,  
                  char **ppath, char **pquery, char **pfrag);
```

```
int OSSL_HTTP_parse_url(const char *url,  
                       int *pssl, char **puser, char **phost,  
                       char **pport, int *pport_num,  
                       char **ppath, char **pquery, char **pfrag);
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining OPENSSL\_API\_COMPAT with a suitable version value, see openssl\_user\_macros(7):

```
int OCSP_parse_url(const char *url, char **phost, char **pport, char **ppath,
                  int *pssl);
```

## DESCRIPTION

OSSL\_HTTP\_adapt\_proxy() takes an optional proxy hostname proxy and returns it transformed according to the optional no\_proxy parameter, server, use\_ssl, and the applicable environment variable, as follows. If proxy is NULL, take any default value from the "http\_proxy" environment variable, or from "https\_proxy" if use\_ssl is nonzero. If this still does not yield a proxy hostname, take any further default value from the "HTTP\_PROXY" environment variable, or from "HTTPS\_PROXY" if use\_ssl is nonzero. If no\_proxy is NULL, take any default exclusion value from the "no\_proxy" environment variable, or else from "NO\_PROXY". Return the determined proxy hostname unless the exclusion contains server. Otherwise return NULL.

OSSL\_parse\_url() parses its input string url as a URL of the form "[scheme://][userinfo@]host[:port][/path][?query][#fragment]" and splits it up into scheme, userinfo, host, port, path, query, and fragment components. The host (or server) component may be a DNS name or an IP address where IPv6 addresses should be enclosed in square brackets "[" and "]". The port component is optional and defaults to 0. If given, it must be in decimal form. If the pport\_num argument is not NULL the integer value of the port number is assigned to \*pport\_num on success. The path component is also optional and defaults to "/". Each non-NULL result pointer argument pscheme, puser, phost, pport, ppath, pquery, and pfrag, is assigned the respective url component. On success, they are guaranteed to contain non-NULL string pointers, else NULL. It is the responsibility of the caller to free them using OPENSSL\_free(3). If pquery is NULL, any given query component is handled as part of the path. A string returned via \*ppath is guaranteed to begin with a "/" character. For absent scheme, userinfo,

port, query, and fragment components an empty string is provided.

`OSSL_HTTP_parse_url()` is a special form of `OSSL_parse_url()` where the scheme, if given, must be "http" or "https". If `psl` is not NULL, `*psl` is assigned 1 in case parsing was successful and the scheme is "https", else 0. The port component is optional and defaults to 443 if the scheme is "https", else 80. Note that relative paths must be given with a leading "/", otherwise the first path element is interpreted as the hostname.

Calling the deprecated function `OCSP_parse_url(url, host, port, path, ssl)` is equivalent to `OSSL_HTTP_parse_url(url, ssl, NULL, host, port, NULL, path, NULL, NULL)`.

## RETURN VALUES

`OSSL_HTTP_adapt_proxy()` returns NULL if no proxy is to be used, otherwise a constant proxy hostname string, which is either the proxy name handed in or an environment variable value.

`OSSL_parse_url()`, `OSSL_HTTP_parse_url()`, and `OCSP_parse_url()` return 1 on success, 0 on error.

## SEE ALSO

`OSSL_HTTP_transfer(3)`

## HISTORY

`OSSL_HTTP_adapt_proxy()`, `OSSL_parse_url()` and `OSSL_HTTP_parse_url()` were added in OpenSSL 3.0. `OCSP_parse_url()` was deprecated in OpenSSL 3.0.

## COPYRIGHT

Copyright 2019-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                    2023-07-13    OSSL\_HTTP\_PARSE\_URL(3ossl)