



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'PKCS12_add_localkeyid.3ossl' command

\$ man PKCS12_add_localkeyid.3ossl

PKCS12_ADD_LOCALKEYID(3ossl) OpenSSL PKCS12_ADD_LOCALKEYID(3ossl)

NAME

PKCS12_add_localkeyid - Add the localKeyId attribute to a PKCS#12
safeBag

SYNOPSIS

```
#include <openssl/pkcs12.h>

int PKCS12_add_localkeyid(PKCS12_SAFEBAG *bag, const char *name,
                          int namelen);
```

DESCRIPTION

PKCS12_add_localkeyid() adds an octet string representation of the
PKCS#9 localKeyId attribute to a PKCS#12 safeBag.

bag is the PKCS12_SAFEBAG to add the attribute to.

RETURN VALUES

Returns 1 for success or 0 for failure.

SEE ALSO

PKCS12_add_friendlyname_asc(3)

COPYRIGHT

Copyright 2019 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 PKCS12_ADD_LOCALKEYID(3ossl)