



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'RAND_cleanup.3oss1' command

\$ man RAND_cleanup.3oss1

RAND_CLEANUP(3oss1) OpenSSL RAND_CLEANUP(3oss1)

NAME

RAND_cleanup - erase the PRNG state

SYNOPSIS

```
#include <openssl/rand.h>
```

The following function has been deprecated since OpenSSL 1.1.0, and can be hidden entirely by defining OPENSSL_API_COMPAT with a suitable version value, see openssl_user_macros(7):

```
void RAND_cleanup(void);
```

DESCRIPTION

Prior to OpenSSL 1.1.0, RAND_cleanup() released all resources used by the PRNG. As of version 1.1.0, it does nothing and should not be called, since no explicit initialisation or de-initialisation is necessary. See OPENSSL_init_crypto(3).

RETURN VALUES

RAND_cleanup() returns no value.

SEE ALSO

RAND(7)

HISTORY

RAND_cleanup() was deprecated in OpenSSL 1.1.0; do not use it. See
OPENSSL_init_crypto(3)

COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use
this file except in compliance with the License. You can obtain a copy
in the file LICENSE in the source distribution or at
<<https://www.openssl.org/source/license.html>>.

3.0.7 2023-07-13 RAND_CLEANUP(3ossl)