



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'SSL_SESSION_get0_peer.3oss!' command

```
$ man SSL_SESSION_get0_peer.3oss!
```

```
SSL_SESSION_GET0_PEER(3ossl)  OpenSSL  SSL_SESSION_GET0_PEER(3ossl)
```

NAME

SSL_SESSION_get0_peer - get details about peer's certificate for a session

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
X509 *SSL_SESSION_get0_peer(SSL_SESSION *s);
```

DESCRIPTION

SSL_SESSION_get0_peer() returns the peer certificate associated with the session s or NULL if no peer certificate is available. The caller should not free the returned value (unless X509_up_ref(3) has also been called).

RETURN VALUES

SSL_SESSION_get0_peer() returns a pointer to the peer certificate or NULL if no peer certificate is available.

SEE ALSO

ssl(7)

COPYRIGHT

Copyright 2017 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 SSL_SESSION_GET0_PEER(3ossl)