



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'SSL_has_pending.3oss1' command

\$ man SSL_has_pending.3oss1

SSL_PENDING(3oss1) OpenSSL SSL_PENDING(3oss1)

NAME

SSL_pending, SSL_has_pending - check for readable bytes buffered in an SSL object

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
int SSL_pending(const SSL *ssl);
```

```
int SSL_has_pending(const SSL *s);
```

DESCRIPTION

Data is received in whole blocks known as records from the peer. A whole record is processed (e.g. decrypted) in one go and is buffered by OpenSSL until it is read by the application via a call to `SSL_read_ex(3)` or `SSL_read(3)`.

`SSL_pending()` returns the number of bytes which have been processed, buffered and are available inside `ssl` for immediate read.

If the SSL object's `read_ahead` flag is set (see `SSL_CTX_set_read_ahead(3)`), additional protocol bytes (beyond the

current record) may have been read containing more TLS/SSL records. This also applies to DTLS and pipelining (see `SSL_CTX_set_split_send_fragment(3)`). These additional bytes will be buffered by OpenSSL but will remain unprocessed until they are needed. As these bytes are still in an unprocessed state `SSL_pending()` will ignore them. Therefore, it is possible for no more bytes to be readable from the underlying BIO (because OpenSSL has already read them) and for `SSL_pending()` to return 0, even though readable application data bytes are available (because the data is in unprocessed buffered records).

`SSL_has_pending()` returns 1 if `s` has buffered data (whether processed or unprocessed) and 0 otherwise. Note that it is possible for `SSL_has_pending()` to return 1, and then a subsequent call to `SSL_read_ex()` or `SSL_read()` to return no data because the unprocessed buffered data when processed yielded no application data (for example this can happen during renegotiation). It is also possible in this scenario for `SSL_has_pending()` to continue to return 1 even after an `SSL_read_ex()` or `SSL_read()` call because the buffered and unprocessed data is not yet processable (e.g. because OpenSSL has only received a partial record so far).

RETURN VALUES

`SSL_pending()` returns the number of buffered and processed application data bytes that are pending and are available for immediate read.

`SSL_has_pending()` returns 1 if there is buffered record data in the SSL object and 0 otherwise.

SEE ALSO

`SSL_read_ex(3)`, `SSL_read(3)`, `SSL_CTX_set_read_ahead(3)`,
`SSL_CTX_set_split_send_fragment(3)`, `ssl(7)`

HISTORY

The `SSL_has_pending()` function was added in OpenSSL 1.1.0.

COPYRIGHT

Copyright 2000-2020 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7

2023-07-13

SSL_PENDING(3ossl)