



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'SSL_want_client_hello_cb.3ossl' command

```
$ man SSL_want_client_hello_cb.3ossl
```

```
SSL_WANT(3ossl)          OpenSSL          SSL_WANT(3ossl)
```

NAME

SSL_want, SSL_want_nothing, SSL_want_read, SSL_want_write,
SSL_want_x509_lookup, SSL_want_retry_verify, SSL_want_async,
SSL_want_async_job, SSL_want_client_hello_cb - obtain state information
TLS/SSL I/O operation

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
int SSL_want(const SSL *ssl);  
int SSL_want_nothing(const SSL *ssl);  
int SSL_want_read(const SSL *ssl);  
int SSL_want_write(const SSL *ssl);  
int SSL_want_x509_lookup(const SSL *ssl);  
int SSL_want_retry_verify(const SSL *ssl);  
int SSL_want_async(const SSL *ssl);  
int SSL_want_async_job(const SSL *ssl);  
int SSL_want_client_hello_cb(const SSL *ssl);
```

DESCRIPTION

SSL_want() returns state information for the SSL object ssl.

The other `SSL_want_*`() calls are shortcuts for the possible states returned by `SSL_want()`.

NOTES

`SSL_want()` examines the internal state information of the SSL object. Its return values are similar to that of `SSL_get_error(3)`. Unlike `SSL_get_error(3)`, which also evaluates the error queue, the results are obtained by examining an internal state flag only. The information must therefore only be used for normal operation under nonblocking I/O. Error conditions are not handled and must be treated using `SSL_get_error(3)`.

The result returned by `SSL_want()` should always be consistent with the result of `SSL_get_error(3)`.

RETURN VALUES

The following return values can currently occur for `SSL_want()`:

SSL_NOTHING

There is no data to be written or to be read.

SSL_WRITING

There are data in the SSL buffer that must be written to the underlying BIO layer in order to complete the actual `SSL_*`() operation. A call to `SSL_get_error(3)` should return `SSL_ERROR_WANT_WRITE`.

SSL_READING

More data must be read from the underlying BIO layer in order to complete the actual `SSL_*`() operation. A call to `SSL_get_error(3)` should return `SSL_ERROR_WANT_READ`.

SSL_X509_LOOKUP

The operation did not complete because an application callback set by `SSL_CTX_set_client_cert_cb()` has asked to be called again. A call to `SSL_get_error(3)` should return `SSL_ERROR_WANT_X509_LOOKUP`.

SSL_RETRY_VERIFY

The operation did not complete because a certificate verification callback has asked to be called again via `SSL_set_retry_verify(3)`.

A call to `SSL_get_error(3)` should return `SSL_ERROR_WANT_RETRY_VERIFY`.

SSL_ASYNC_PAUSED

An asynchronous operation partially completed and was then paused.

See `SSL_get_all_async_fds(3)`. A call to `SSL_get_error(3)` should return `SSL_ERROR_WANT_ASYNC`.

SSL_ASYNC_NO_JOBS

The asynchronous job could not be started because there were no async jobs available in the pool (see `ASYNC_init_thread(3)`). A call to `SSL_get_error(3)` should return `SSL_ERROR_WANT_ASYNC_JOB`.

SSL_CLIENT_HELLO_CB

The operation did not complete because an application callback set by `SSL_CTX_set_client_hello_cb()` has asked to be called again. A call to `SSL_get_error(3)` should return `SSL_ERROR_WANT_CLIENT_HELLO_CB`.

`SSL_want_nothing()`, `SSL_want_read()`, `SSL_want_write()`, `SSL_want_x509_lookup()`, `SSL_want_retry_verify()`, `SSL_want_async()`, `SSL_want_async_job()`, and `SSL_want_client_hello_cb()` return 1 when the corresponding condition is true or 0 otherwise.

ssl(7), SSL_get_error(3)

HISTORY

The SSL_want_client_hello_cb() function and the SSL_CLIENT_HELLO_CB return value were added in OpenSSL 1.1.1.

COPYRIGHT

Copyright 2001-2022 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 SSL_WANT(3ossl)