



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'X509\_ALGOR\_cmp.3ossl' command**

**\$ man X509\_ALGOR\_cmp.3ossl**

X509\_ALGOR\_DUP(3ossl)          OpenSSL          X509\_ALGOR\_DUP(3ossl)

### NAME

X509\_ALGOR\_dup, X509\_ALGOR\_set0, X509\_ALGOR\_get0, X509\_ALGOR\_set\_md,  
X509\_ALGOR\_cmp, X509\_ALGOR\_copy - AlgorithmIdentifier functions

### SYNOPSIS

```
#include <openssl/x509.h>
```

```
X509_ALGOR *X509_ALGOR_dup(X509_ALGOR *alg);  
int X509_ALGOR_set0(X509_ALGOR *alg, ASN1_OBJECT *aobj, int ptype, void *pval);  
void X509_ALGOR_get0(const ASN1_OBJECT **paobj, int *pptype,  
                      const void **ppval, const X509_ALGOR *alg);  
void X509_ALGOR_set_md(X509_ALGOR *alg, const EVP_MD *md);  
int X509_ALGOR_cmp(const X509_ALGOR *a, const X509_ALGOR *b);  
int X509_ALGOR_copy(X509_ALGOR *dest, const X509_ALGOR *src);
```

### DESCRIPTION

X509\_ALGOR\_dup() returns a copy of alg.

X509\_ALGOR\_set0() sets the algorithm OID of alg to aobj and the associated parameter type to ptype with value pval. If ptype is

V\_ASN1\_UNDEF the parameter is omitted, otherwise ptype and pval have

the same meaning as the type and value parameters to ASN1\_TYPE\_set(). All the supplied parameters are used internally so must NOT be freed after this call.

X509\_ALGOR\_get0() is the inverse of X509\_ALGOR\_set0(): it returns the algorithm OID in \*paobj and the associated parameter in \*pptype and \*ppval from the AlgorithmIdentifier alg.

X509\_ALGOR\_set\_md() sets the AlgorithmIdentifier alg to appropriate values for the message digest md.

X509\_ALGOR\_cmp() compares a and b and returns 0 if they have identical encodings and nonzero otherwise.

X509\_ALGOR\_copy() copies the source values into the dest structs; making a duplicate of each (and free any thing pointed to from within \*dest).

## RETURN VALUES

X509\_ALGOR\_dup() returns a valid X509\_ALGOR structure or NULL if an error occurred.

X509\_ALGOR\_set0() and X509\_ALGOR\_copy() return 1 on success or 0 on error.

X509\_ALGOR\_get0() and X509\_ALGOR\_set\_md() return no values.

X509\_ALGOR\_cmp() returns 0 if the two parameters have identical encodings and nonzero otherwise.

## HISTORY

The X509\_ALGOR\_copy() was added in 1.1.1e.

## COPYRIGHT

Copyright 2002-2020 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                    2023-07-13            X509\_ALGOR\_DUP(3ossl)