



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'acosh.3p' command

\$ man acosh.3p

ACOSH(3P) POSIX Programmer's Manual ACOSH(3P)

PROLOG

This manual page is part of the POSIX Programmer's Manual. The Linux implementation of this interface may differ (consult the corresponding Linux manual page for details of Linux behavior), or the interface may not be implemented on Linux.

NAME

acosh, acoshf, acoshl ? inverse hyperbolic cosine functions

SYNOPSIS

```
#include <math.h>

double acosh(double x);

float acoshf(float x);

long double acoshl(long double x);
```

DESCRIPTION

The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of POSIX.1?2017 defers to the ISO C standard.

These functions shall compute the inverse hyperbolic cosine of their argument x .

An application wishing to check for error situations should set `errno` to zero and call `feclearexcept(FE_ALL_EXCEPT)` before calling these functions. On return, if `errno` is non-zero or `fetestexcept(FE_INVALID |`

FE_DIVBYZERO | FE_OVERFLOW | FE_UNDERFLOW) is non-zero, an error has occurred.

RETURN VALUE

Upon successful completion, these functions shall return the inverse hyperbolic cosine of their argument.

For finite values of $x < 1$, a domain error shall occur, and either a NaN (if supported), or an implementation-defined value shall be returned.

If x is NaN, a NaN shall be returned.

If x is $+1$, $+0$ shall be returned.

If x is $+\text{Inf}$, $+\text{Inf}$ shall be returned.

If x is $-\text{Inf}$, a domain error shall occur, and a NaN shall be returned.

ERRORS

These functions shall fail if:

Domain Error

The x argument is finite and less than $+1.0$, or is $-\text{Inf}$.

If the integer expression $(\text{math_errhandling} \ \& \ \text{MATH_ERRNO})$ is non-zero, then `errno` shall be set to `[EDOM]`. If the integer expression $(\text{math_errhandling} \ \& \ \text{MATH_ERREXCEPT})$ is non-zero, then the invalid floating-point exception shall be raised.

The following sections are informative.

EXAMPLES

None.

APPLICATION USAGE

On error, the expressions $(\text{math_errhandling} \ \& \ \text{MATH_ERRNO})$ and $(\text{math_errhandling} \ \& \ \text{MATH_ERREXCEPT})$ are independent of each other, but at least one of them must be non-zero.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

cosh(), feclearexcept(), fetestexcept()

The Base Definitions volume of POSIX.1-2017, Section 4.20, Treatment of Error Conditions for Mathematical Functions, <math.h>

COPYRIGHT

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1-2017, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 7, 2018 Edition, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html>.

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see https://www.kernel.org/doc/man-pages/reporting_bugs.html.

IEEE/The Open Group

2017

ACOSH(3P)