



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'avahi-daemon.conf.5' command

\$ man avahi-daemon.conf.5

avahi-daemon.conf(5) File Formats Manual avahi-daemon.conf(5)

NAME

avahi-daemon.conf - avahi-daemon configuration file

SYNOPSIS

/etc/avahi/avahi-daemon.conf

DESCRIPTION

avahi-daemon.conf is the configuration file for avahi-daemon.

SECTION [SERVER]

host-name= Set the host name avahi-daemon tries to register on the LAN.

If omitted defaults to the system host name as set with the sethost?

name() system call.

host-name-from-machine-id= Takes a boolean value ("yes" or "no"). If

set to "yes" avahi-daemon will use the machine-id as name on the LAN.

domain-name= Set the default domain name avahi-daemon tries to register

its host name and services on the LAN in. If omitted defaults to ".lo?

cal".

browse-domains= Set a comma separated list of browsing domains (in ad?

dition to the default one and those announced inside the default brows?

ing domain). Please note that the user may specify additional browsing

domains on the client side, either by setting \$AVAHIBROWSE_DOMAINS to

a list of colon separated domains or by adding them to the XDG config

file ~/.config/avahi/browse-domains (separated by newlines).

use-ipv4= Takes a boolean value ("yes" or "no"). If set to "no" avahi-

daemon will not use IPv4 sockets. Default is "yes".

use-ipv6= Takes a boolean value ("yes" or "no"). If set to "no" avahi-

daemon will not use IPv6 sockets. Default is "yes".

allow-interfaces= Set a comma separated list of allowed network inter?

faces that should be used by the avahi-daemon. Traffic on other inter?

faces will be ignored. If set to an empty list all local interfaces ex?

cept loopback and point-to-point will be used.

deny-interfaces= Set a comma separated list of network interfaces that

should be ignored by avahi-daemon. Other not specified interfaces will

be used, unless allow-interfaces= is set. This option takes precedence

over allow-interfaces=.

check-response-ttl= Takes a boolean value ("yes" or "no"). If set to

"yes", an additional security check is activated: incoming IP packets

will be ignored unless the IP TTL is 255. Earlier mDNS specifications

required this check. Since this feature may be incompatible with newer

implementations of mDNS it defaults to "no". On the other hand it pro?

vides extra security.

use-iff-running= Takes a boolean value ("yes" or "no"). If set to "yes"

avahi-daemon monitors the IFF_RUNNING flag bit which is used by some

(modern) network drivers to tell user space if a network cable is

plugged in (in case of copper ethernet), or the network card is associ?

ated with some kind of network (in case of WLAN). If IFF_RUNNING is set

avahi-daemon will automatically announce its services on that network.

Unfortunately far too many network drivers do not support this flag or

support it in a broken way. Therefore this option defaults to "no".

enable-dbus= Takes either "yes", "no" or "warn". If set to "yes" avahi-

daemon connects to D-Bus, offering an object oriented client API. It is

only available if Avahi has been compiled with --enable-dbus in which

case it defaults to "yes". "warn" behaves like "yes", but the daemon

starts up even when it fails to connect to a D-Bus daemon. In addition,

if the connection to the D-Bus daemon is terminated we try to recon?

nect. (Unless we are in a chroot() environment where this definitely

will fail.)

disallow-other-stacks= Takes a boolean value ("yes" or "no"). If set to "yes" no other process is allowed to bind to UDP port 5353. This effectively impedes other mDNS stacks from running on the host. Use this as a security measure to make sure that only Avahi is responsible for mDNS traffic. Please note that we do not recommend running multiple mDNS stacks on the same host simultaneously. This hampers reliability and is a waste of resources. However, to not annoy people this option defaults to "no".

allow-point-to-point= Takes a boolean value ("yes" or "no"). If set to "yes" avahi-daemon will make use of interfaces with the POINTOPOINT flag set. This option defaults to "no" as it might make mDNS unreliable due to usually large latencies with such links and opens a potential security hole by allowing mDNS access from Internet connections. Use with care and YMMV!

cache-entries-max= Takes an unsigned integer specifying how many resource records are cached per interface. Bigger values allow mDNS work correctly in large LANs but also increase memory consumption.

clients-max= Takes an unsigned integer. The maximum number of concurrent D-Bus clients allowed. If the maximum number is reached further clients will be refused until at least one existing client disconnects.

objects-per-client-max= Takes an unsigned integer. The maximum number of objects (entry groups, browsers, resolvers) that may be registered per D-Bus client at a time. If the maximum number is reached further object creation will be refused until at least one object is freed.

entries-per-entry-group-max= Takes an unsigned integer. The maximum number of entries (resource records) per entry group registered by a D-Bus client at a time. If the maximum number is reached further resource records may not be added to an entry group.

ratelimit-interval-usec= Takes an unsigned integer. Sets the per-interface packet rate-limiting interval parameter. Together with ratelimit-burst= this may be used to control the maximum number of packets Avahi will generate in a specific period of time on an interface.

ratelimit-burst= Takes an unsigned integer. Sets the per-interface

packet rate-limiting burst parameter. Together with ratelimit-interval-usec= this may be used to control the maximum number of packets Avahi will generate in a specific period of time on an interface.

SECTION [WIDE-AREA]

enable-wide-area= Takes a boolean value ("yes" or "no"). Enable wide-area DNS-SD, aka DNS-SD over unicast DNS. If this is enabled only domains ending in .local will be resolved on mDNS, all other domains are resolved via unicast DNS. If you want to maintain multiple different multicast DNS domains even with this option enabled we encourage you to use subdomains of .local, such as "kitchen.local". This option defaults to "yes".

SECTION [PUBLISH]

disable-publishing= Takes a boolean value ("yes" or "no"). If set to "yes", no record will be published by Avahi, not even address records for the local host. Avahi will be started in a querying-only mode. Use this is a security measure. This option defaults to "no".

disable-user-service-publishing= Takes a boolean value ("yes" or "no"). If set to "yes", Avahi will still publish address records and suchlike but will not allow user applications to publish services. Use this is a security measure. This option defaults to "no".

add-service-cookie= Takes a boolean value ("yes" or "no"). If set to "yes" an implicit TXT entry will be added to all locally registered services, containing a cookie value which is chosen randomly on daemon startup. This can be used to detect if two services on two different interfaces/protocols are actually identical. Defaults to "no".

publish-addresses= Takes a boolean value ("yes" or "no"). If set to "yes" avahi-daemon will register mDNS address records for all local IP addresses. Unless you want to use avahi-daemon exclusively for browsing it's recommended to enable this. If you plan to register local services you need to enable this option. Defaults to "yes".

publish-hinfo= Takes a boolean value ("yes" or "no"). If set to "yes" avahi-daemon will register an mDNS HINFO record on all interfaces which contains information about the local operating system and CPU, which

might be useful for administrative purposes. This is recommended by the mDNS specification but not required. For the sake of privacy you might choose to disable this feature. Defaults to "no".

publish-workstation= Takes a boolean value ("yes" or "no"). If set to "yes" avahi-daemon will register a service of type "_workstation._tcp" on the local LAN. This might be useful for administrative purposes (i.e. browse for all PCs on the LAN), but is not required or recommended by any specification. Newer MacOS X releases register a service of this type. Defaults to "no".

publish-domain= Takes a boolean value ("yes" or "no"). If set to "yes" avahi-daemon will announce the locally used domain name (see above) for browsing by other hosts. Defaults to "yes".

publish-dns-servers= Takes a comma separated list of IP addresses for unicast DNS servers. You can use this to announce unicast DNS servers via mDNS. When used in conjunction with avahi-dnsconfd on the client side this allows DHCP-like configuration of unicast DNS servers.

publish-resolv-conf-dns-servers= Takes a boolean value ("yes" or "no"). If set to "yes" avahi-daemon will publish the unicast DNS servers specified in /etc/resolv.conf in addition to those specified with publish-dns-servers. Send avahi-daemon a SIGHUP to have it reload this file. Defaults to "no".

publish-aaaa-on-ipv4= Takes a boolean value ("yes" or "no"). If set to "yes" avahi-daemon will publish an IPv6 AAAA record via IPv4, i.e. the local IPv6 addresses can be resolved using an IPv4 transport. Only useful when IPv4 is enabled with use-ipv4=true. Defaults to "yes".

publish-a-on-ipv6= Takes a boolean value ("yes" or "no"). If set to "yes" avahi-daemon will publish an IPv4 A record via IPv6, i.e. the local IPv4 addresses can be resolved using an IPv6 transport. Only useful when IPv6 is enabled with use-ipv6=true. Defaults to "no".

SECTION [REFLECTOR]

enable-reflector= Takes a boolean value ("yes" or "no"). If set to "yes" avahi-daemon will reflect incoming mDNS requests to all local network interfaces, effectively allowing clients to browse mDNS/DNS-SD

services on all networks connected to the gateway. The gateway is some? what intelligent and should work with all kinds of mDNS traffic, though some functionality is lost (specifically the unicast reply bit, which is used rarely anyway). Make sure to not run multiple reflectors between the same networks, this might cause them to play Ping Pong with mDNS packets. Defaults to "no".

reflect-ipv= Takes a boolean value ("yes" or "no"). If set to "yes" and enable-reflector is enabled, avahi-daemon will forward mDNS traffic between IPv4 and IPv6, which is usually not recommended. Defaults to "no".

reflect-filters= Set a comma separated list of allowed service names to be reflected. Each service that is seen must match an entry in this list to be reflected to other networks. This list can match the type of service or the name of the machine providing the service. Defaults to allowing all services.

SECTION [RLIMITS]

This section is used to define system resource limits for the daemon.

See `setrlimit(2)` for more information. If any of the options is not specified in the configuration file, avahi-daemon does not change it from the system defaults.

rlimit-as= Value in bytes for `RLIMIT_AS` (maximum size of the process's virtual memory). Sensible values are heavily system dependent.

rlimit-core= Value in bytes for `RLIMIT_CORE` (maximum core file size).

Unless you want to debug avahi-daemon, it is safe to set this to 0.

rlimit-data= Value in bytes for `RLIMIT_DATA` (maximum size of the process's data segment). Sensible values are heavily system dependent.

rlimit-fsize= Value for `RLIMIT_FSIZE` (maximum size of files the process may create). Since avahi-daemon shouldn't write any files to disk, it is safe to set this to 0.

rlimit-nofile= Value for `RLIMIT_NOFILE` (open file descriptors). avahi-daemon shouldn't need more than 15 to 20 open file descriptors concurrently.

rlimit-stack= Value in bytes for `RLIMIT_STACK` (maximum size of the

process stack). Sensible values are heavily system dependent.

rlimit-nproc= Value for RLIMIT_NPROC (max number of processes a user can launch). avahi-daemon forks of a helper process on systems where chroot(2) is available therefore this value should not be set below 2.

Note that while the process limit only applies to this process, the total count of processes to reach that limit includes all processes on the system with the same UID, including any containers without UID remapping (such as lxd containers with security.privileged=true). The default configuration of 3 was removed to prevent problems in this scenario.

AUTHORS

The Avahi Developers <avahi (at) lists (dot) freedesktop (dot) org>;

Avahi is available from <http://avahi.org/>

SEE ALSO

[avahi-daemon\(8\)](#), [avahi-dnsconfd\(8\)](#)

COMMENTS

This man page was written using [xml2man\(1\)](#) by Oliver Kurth.

Manuals

User

[avahi-daemon.conf\(5\)](#)