



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'buildah-login.1' command

\$ man buildah-login.1

buildah-login(1) General Commands Manual buildah-login(1)

NAME

buildah-login - Login to a container registry

SYNOPSIS

buildah login [options] registry

DESCRIPTION

buildah login logs into a specified registry server with the correct username and password. buildah login reads in the username and password from STDIN. The username and password can also be set using the user? name and password flags. The path of the authentication file can be specified by the user by setting the authfile flag. The default path used is \${XDG_RUNTIME_DIR}/containers/auth.json. If XDG_RUNTIME_DIR is not set, the default is /run/containers/\$UID/auth.json.

buildah [GLOBAL OPTIONS]

buildah login [GLOBAL OPTIONS]

buildah login [OPTIONS] REGISTRY [GLOBAL OPTIONS]

OPTIONS

--authfile

Path of the authentication file. Default is \${XDG_RUNTIME_DIR}/containers/auth.json. If XDG_RUNTIME_DIR is not set, the default is /run/containers/\$UID/auth.json. This file is created using buildah login.

Note: You can also override the default path of the authentication file

by setting the `REGISTRY_AUTH_FILE` environment variable. `export REG?`

`ISTRY_AUTH_FILE=path`

`--cert-dir path`

Use certificates at path (*.crt, *.cert, *.key) to connect to the reg?

istry. The default certificates directory is `/etc/containers/certs.d`.

`--get-login`

Return the logged-in user for the registry. Return error if no login is found.

`--help, -h`

Print usage statement

`--password, -p`

Password for registry

`--password-stdin`

Take the password from stdin

`--tls-verify`

Require HTTPS and verification of certificates when talking to con?

tainer registries (default: true). If explicitly set to true, then TLS

verification will be used. If set to false, then TLS verification will

not be used. If not specified, TLS verification will be used unless the

target registry is listed as an insecure registry in `registries.conf`.

TLS verification cannot be used when talking to an insecure registry.

`--username, -u`

Username for registry

`--verbose, -v`

print detailed information about credential store

EXAMPLES

```
$ buildah login quay.io
```

```
Username: qiwanredhat
```

```
Password:
```

```
Login Succeeded!
```

```
$ buildah login -u testuser -p testpassword localhost:5000
```

```
Login Succeeded!
```

```
$ buildah login --authfile ./auth.json quay.io
```

Username: qiwanredhat

Password:

Login Succeeded!

```
$ buildah login --tls-verify=false -u test -p test localhost:5000
```

Login Succeeded!

```
$ buildah login --cert-dir /etc/containers/certs.d/ -u foo -p bar localhost:5000
```

Login Succeeded!

```
$ buildah login -u testuser --password-stdin < pw.txt quay.io
```

Login Succeeded!

```
$ echo $testpassword | buildah login -u testuser --password-stdin quay.io
```

Login Succeeded!

SEE ALSO

[buildah\(1\)](#), [buildah-logout\(1\)](#)

[buildah](#)

Apr 2019

[buildah-login\(1\)](#)