



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'buildah-manifest-exists.1' command**

**\$ man buildah-manifest-exists.1**

buildah-manifest-exists(1)() buildah-manifest-exists(1)()

### **NAME**

buildah-manifest-exists - Check if the given manifest exists in local storage

### **SYNOPSIS**

buildah manifest exists manifest

### **DESCRIPTION**

buildah manifest exists checks if a manifest list exists in local storage. Buildah will return an exit code of 0 when the manifest list is found. A 1 will be returned otherwise. An exit code of 125 indicates there was another issue.

### **OPTIONS**

--help, -h

Print usage statement.

### **EXAMPLE**

Check if a manifest list called list1 exists (the manifest list does actually exist).

```
$ buildah manifest exists list1
```

```
$ echo $?
```

```
0
```

```
$
```

Check if a manifest called mylist exists (the manifest list does not actually exist).

```
$ buildah manifest exists mylist
```

```
$ echo $?
```

```
1
```

```
$
```

## SEE ALSO

[buildah\(1\)](#), [buildah-manifest\(1\)](#)

[buildah-manifest-exists\(1\)\(\)](#)