



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'cancel.1' command

\$ man cancel.1

cancel(1) OpenPrinting cancel(1)

NAME

cancel - cancel jobs

SYNOPSIS

```
cancel [ -h hostname[:port] ] [ -E ] [ -U username ] [ -a ] [ -u user?
name ] [ -x ] [ id ] [ destination ] [ destination-id ]
```

DESCRIPTION

The cancel command cancels print jobs. If no destination or id is specified, the currently printing job on the default destination is canceled.

OPTIONS

The following options are recognized by cancel:

-a Cancel all jobs on the named destination, or all jobs on all destinations if none is provided.

-E Forces encryption when connecting to the server.

-h hostname[:port]

Specifies an alternate server. Note: This option must occur before all others.

-U username

Specifies the username to use when connecting to the server.

-u username

Cancels jobs owned by username.

-x Deletes job data files in addition to canceling.

CONFORMING TO

Unlike the System V printing system, CUPS allows printer names to contain any printable character except SPACE, TAB, "/", or "#". Also, printer and class names are not case-sensitive.

EXAMPLES

Cancel the current print job:

```
cancel
```

Cancel job "myprinter-42":

```
cancel myprinter-42
```

Cancel all jobs:

```
cancel -a
```

NOTES

Administrators wishing to prevent unauthorized cancellation of jobs via the `-u` option should require authentication for Cancel-Jobs operations in `cupsd.conf(5)`.

SEE ALSO

`cupsd.conf(5)`, `lp(1)`, `lpmove(8)`, `lpstat(1)`, CUPS Online Help (<http://localhost:631/help>)

COPYRIGHT

Copyright ? 2007-2019 by Apple Inc.

2022-05-02

CUPS

cancel(1)