



## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'cockpit.1' command***

### ***\$ man cockpit.1***

COCKPIT(1) cockpit COCKPIT(1)

#### NAME

cockpit - Cockpit

#### DESCRIPTION

Cockpit is a web accessible interactive admin interface for Linux machines. Cockpit can usually be accessed on port 9090 of the machine it's installed on. Cockpit starts on demand. Use your system credentials to log in.

#### COMPONENTS

The cockpit-ws web service listens on port 9090 and is started on demand by systemd. The Cockpit web service authenticates the user, loads Cockpit into the browser, and starts cockpit-bridge in a Linux user session.

The cockpit-bridge provides Cockpit in the web browser with access to the system APIs. It does this over its standard in and standard out.

The bridge is started like a shell once per Linux user session.

#### BUGS

Please send bug reports to either the distribution bug tracker or the upstream bug tracker[1].

#### AUTHOR

Cockpit has been written by many contributors[2].

#### SEE ALSO

Cockpit Guide[3], cockpit-ws(8), cockpit-bridge(1), cockpit.conf(5),

systemd(1)

## NOTES

### 1. upstream bug tracker

<https://github.com/cockpit-project/cockpit/issues/new>

### 2. contributors

<https://github.com/cockpit-project/cockpit/>

### 3. Cockpit Guide

<https://cockpit-project.org/guide/latest/>

cockpit

05/16/2023

COCKPIT(1)