



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'endnetent.3p' command***

***\$ man endnetent.3p***

ENDNETENT(3P)          POSIX Programmer's Manual          ENDNETENT(3P)

### PROLOG

This manual page is part of the POSIX Programmer's Manual. The Linux implementation of this interface may differ (consult the corresponding Linux manual page for details of Linux behavior), or the interface may not be implemented on Linux.

### NAME

endnetent, getnetbyaddr, getnetbyname, getnetent, setnetent ? network database functions

### SYNOPSIS

```
#include <netdb.h>

void endnetent(void);

struct netent *getnetbyaddr(uint32_t net, int type);

struct netent *getnetbyname(const char *name);

struct netent *getnetent(void);

void setnetent(int stayopen);
```

### DESCRIPTION

These functions shall retrieve information about networks. This information is considered to be stored in a database that can be accessed sequentially or randomly. The implementation of this database is unspecified.

The setnetent() function shall open and rewind the database. If the stayopen argument is non-zero, the connection to the net database shall

not be closed after each call to `getnetent()` (either directly, or indirectly through one of the other `getnet*()` functions), and the implementation may maintain an open file descriptor to the database.

The `getnetent()` function shall read the next entry of the database, opening and closing a connection to the database as necessary.

The `getnetbyaddr()` function shall search the database from the beginning, and find the first entry for which the address family specified by `type` matches the `n_addrtype` member and the network number `net` matches the `n_net` member, opening and closing a connection to the database as necessary. The `net` argument shall be the network number in host byte order.

The `getnetbyname()` function shall search the database from the beginning and find the first entry for which the network name specified by `name` matches the `n_name` member, opening and closing a connection to the database as necessary.

The `getnetbyaddr()`, `getnetbyname()`, and `getnetent()` functions shall each return a pointer to a `netent` structure, the members of which shall contain the fields of an entry in the network database.

The `endnetent()` function shall close the database, releasing any open file descriptor.

These functions need not be thread-safe.

## RETURN VALUE

Upon successful completion, `getnetbyaddr()`, `getnetbyname()`, and `getnetent()` shall return a pointer to a `netent` structure if the requested entry was found, and a null pointer if the end of the database was reached or the requested entry was not found. Otherwise, a null pointer shall be returned.

The application shall not modify the structure to which the return value points, nor any storage areas pointed to by pointers within the structure. The returned pointer, and pointers within the structure, might be invalidated or the structure or the storage areas might be overwritten by a subsequent call to `getnetbyaddr()`, `getnetbyname()`, or `getnetent()`. The returned pointer, and pointers within the structure,

might also be invalidated if the calling thread is terminated.

## ERRORS

No errors are defined.

The following sections are informative.

## EXAMPLES

None.

## APPLICATION USAGE

None.

## RATIONALE

None.

## FUTURE DIRECTIONS

None.

## SEE ALSO

The Base Definitions volume of POSIX.1?2017, <netdb.h>

## COPYRIGHT

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1-2017, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 7, 2018 Edition, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html> .

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see [https://www.kernel.org/doc/man-pages/reporting\\_bugs.html](https://www.kernel.org/doc/man-pages/reporting_bugs.html) .