



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'exp10f.3' command

\$ man exp10f.3

EXP10(3) Linux Programmer's Manual EXP10(3)

NAME

exp10, exp10f, exp10l - base-10 exponential function

SYNOPSIS

```
#define _GNU_SOURCE       /* See feature_test_macros(7) */
```

```
#include <math.h>
```

```
double exp10(double x);
```

```
float exp10f(float x);
```

```
long double exp10l(long double x);
```

Link with -lm.

DESCRIPTION

These functions return the value of 10 raised to the power of x.

RETURN VALUE

On success, these functions return the base-10 exponential value of x.

For various special cases, including the handling of infinity and NaN, as well as overflows and underflows, see exp(3).

ERRORS

See math_error(7) for information on how to determine whether an error has occurred when calling these functions.

For a discussion of the errors that can occur for these functions, see exp(3).

VERSIONS

These functions first appeared in glibc in version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

??

?Interface ? Attribute ? Value ?

??

?exp10(), exp10f(), exp10l() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

These functions are GNU extensions.

BUGS

Prior to version 2.19, the glibc implementation of these functions did

not set errno to ERANGE when an underflow error occurred.

SEE ALSO

cbrt(3), exp(3), exp2(3), log10(3), sqrt(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A

description of the project, information about reporting bugs, and the

latest version of this page, can be found at

<https://www.kernel.org/doc/man-pages/>.

GNU 2017-09-15 EXP10(3)