



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'fc-scan.1' command

\$ man fc-scan.1

FC-SCAN(1) FC-SCAN(1)

NAME

fc-scan - scan font files or directories

SYNOPSIS

```
fc-scan [ -Vh ]  
[ [ -f format ] [ --format format ] ] [ --version ] [ --help ]  
file...
```

DESCRIPTION

fc-scan scans file(s) recursively and prints out font pattern for each face found.

OPTIONS

This program follows the usual GNU command line syntax, with long options starting with two dashes ('-'). A summary of options is included below.

-f Format output according to the format specifier format.
-V Show version of the program and exit.
-h Show summary of options.
file Scan file recursively for font faces.

RETURN CODES

fc-scan returns error code 0 if at least one font was found or 1 otherwise.

SEE ALSO

fc-query(1) FcFileScan(3) FcDirScan(3) FcPatternFormat(3) fc-cat(1) fc-

cache(1) fc-list(1) fc-match(1) fc-pattern(1)

The fontconfig user's guide, in HTML format: /usr/share/doc/fontcon?

fig/fontconfig-user.html.

AUTHOR

This manual page was updated by Behdad Esfahbod <behdad@behdad.org>.

Jan 15, 2009

FC-SCAN(1)