



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'flatpak-pin.1' command**

**\$ man flatpak-pin.1**

FLATPAK PIN(1) flatpak pin FLATPAK PIN(1)

### NAME

flatpak-pin - Pin runtimes to prevent automatic removal

### SYNOPSIS

flatpak pin [OPTION...] PATTERN...

### DESCRIPTION

Flatpak maintains a list of patterns that define which refs are pinned.

A pinned ref will never be automatically uninstalled (as are unused runtimes periodically). This can be useful if for example you are using a runtime for development purposes.

Runtimes that are explicitly installed, rather than installed as a dependency of something else, are automatically pinned.

The patterns are just a partial ref, with the \* character matching anything within that part of the ref. Only runtimes can be pinned, not apps. Here are some example patterns:

org.some.Runtime

org.some.Runtime//unstable

runtime/org.domain.\*

org.some.Runtime/arm

To list the current set of pins, run this command without any patterns.

### OPTIONS

The following options are understood:

-h, --help

Show help options and exit.

--remove

Instead of adding the patterns, remove matching patterns.

--user

Pin refs in a per-user installation.

--system

Pin refs in the default system-wide installation.

--installation=NAME

Pin refs in a system-wide installation specified by NAME among

those defined in /etc/flatpak/installations.d/. Using

--installation=default is equivalent to using --system.

-v, --verbose

Print debug information during command processing.

## EXAMPLES

\$ flatpak pin

\$ flatpak pin org.freedesktop.Platform//19.08

\$ flatpak pin --remove org.freedesktop.Platform//19.08

## SEE ALSO

flatpak(1), flatpak-uninstall(1),

flatpak

FLATPAK PIN(1)