



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'fputs_unlocked.3' command

\$ man fputs_unlocked.3

UNLOCKED_STDIO(3) Linux Programmer's Manual UNLOCKED_STDIO(3)

NAME

getc_unlocked, getchar_unlocked, putc_unlocked, putchar_unlocked - non?
locking stdio functions

SYNOPSIS

```
#include <stdio.h>

int getc_unlocked(FILE *stream);

int getchar_unlocked(void);

int putc_unlocked(int c, FILE *stream);

int putchar_unlocked(int c);

void clearerr_unlocked(FILE *stream);

int feof_unlocked(FILE *stream);

int ferror_unlocked(FILE *stream);

int fileno_unlocked(FILE *stream);

int fflush_unlocked(FILE *stream);

int fgetc_unlocked(FILE *stream);

int fputc_unlocked(int c, FILE *stream);

size_t fread_unlocked(void *ptr, size_t size, size_t n,
                      FILE *stream);

size_t fwrite_unlocked(const void *ptr, size_t size, size_t n,
                      FILE *stream);

char *fgets_unlocked(char *s, int n, FILE *stream);

int fputs_unlocked(const char *s, FILE *stream);
```

```
#include <wchar.h>

wint_t getwc_unlocked(FILE *stream);

wint_t getwchar_unlocked(void);

wint_t fgetwc_unlocked(FILE *stream);

wint_t fputwc_unlocked(wchar_t wc, FILE *stream);

wint_t putwc_unlocked(wchar_t wc, FILE *stream);

wint_t putwchar_unlocked(wchar_t wc);

wchar_t *fgetws_unlocked(wchar_t *ws, int n, FILE *stream);

int fputws_unlocked(const wchar_t *ws, FILE *stream);
```

Feature Test Macro Requirements for glibc (see `feature_test_macros(7)`):

```
getc_unlocked(), getchar_unlocked(), putc_unlocked(), putchar_un?
locked():

/* Since glibc 2.24: */ _POSIX_C_SOURCE >= 199309L

|| /* Glibc versions <= 2.23: */ _POSIX_C_SOURCE

|| /* Glibc versions <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE

clearerr_unlocked(), feof_unlocked(), ferror_unlocked(), fileno_un?
locked(), fflush_unlocked(), fgetc_unlocked(), fputc_unlocked(),
fread_unlocked(), fwrite_unlocked():

/* Glibc since 2.19: */ _DEFAULT_SOURCE

|| /* Glibc versions <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE

fgets_unlocked(), fputs_unlocked(), getwc_unlocked(), getwchar_un?
locked(), fgetwc_unlocked(), fputwc_unlocked(), putwchar_unlocked(),
fgetws_unlocked(), fputws_unlocked():

_GNU_SOURCE
```

DESCRIPTION

Each of these functions has the same behavior as its counterpart with? out the "_unlocked" suffix, except that they do not use locking (they do not set locks themselves, and do not test for the presence of locks set by others) and hence are thread-unsafe. See `flockfile(3)`.

ATTRIBUTES

For an explanation of the terms used in this section, see `at? tributes(7)`.

??

?Interface	? Attribute	? Value	?
??			
?getc_unlocked(),	? Thread safety	? MT-Safe race:stream	?
?putc_unlocked(),	?	?	?
?clearerr_unlocked(),	?	?	?
?fflush_unlocked(),	?	?	?
?fgetc_unlocked(),	?	?	?
?fputc_unlocked(),	?	?	?
?fread_unlocked(),	?	?	?
?fwrite_unlocked(),	?	?	?
?fgets_unlocked(),	?	?	?
?fputs_unlocked(),	?	?	?
?getwc_unlocked(),	?	?	?
?fgetwc_unlocked(),	?	?	?
?fputwc_unlocked(),	?	?	?
?putwc_unlocked(),	?	?	?
?fgetws_unlocked(),	?	?	?
?fputws_unlocked()	?	?	?
??			
?getchar_unlocked(),	? Thread safety	? MT-Unsafe race:stdin	?
?getwchar_unlocked()	?	?	?
??			
?putchar_unlocked(),	? Thread safety	? MT-Unsafe race:stdout	?
?putwchar_unlocked()	?	?	?
??			
?feof_unlocked(),	? Thread safety	? MT-Safe	?
?ferror_unlocked(),	?	?	?
?fileno_unlocked()	?	?	?
??			

CONFORMING TO

The four functions `getc_unlocked()`, `getchar_unlocked()`, `putc_unlocked()`, `putchar_unlocked()` are in POSIX.1-2001 and POSIX.1-2008.

The nonstandard `*_unlocked()` variants occur on a few UNIX systems, and

are available in recent glibc. They should probably not be used.

SEE ALSO

flockfile(3), stdio(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

UNLOCKED_STDIO(3)