



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'i2d_PKCS8PrivateKey_nid_fp.3oss!' command

```
$ man i2d_PKCS8PrivateKey_nid_fp.3oss!
```

```
D2I_PKCS8PRIVATEKEY_BIO(3oss!)  OpenSSL  D2I_PKCS8PRIVATEKEY_BIO(3oss!)
```

NAME

```
d2i_PKCS8PrivateKey_bio, d2i_PKCS8PrivateKey_fp,  
i2d_PKCS8PrivateKey_bio, i2d_PKCS8PrivateKey_fp,  
i2d_PKCS8PrivateKey_nid_bio, i2d_PKCS8PrivateKey_nid_fp - PKCS#8 format  
private key functions
```

SYNOPSIS

```
#include <openssl/evp.h>
```

```
EVP_PKEY *d2i_PKCS8PrivateKey_bio(BIO *bp, EVP_PKEY **x, pem_password_cb *cb, void *u);
```

```
EVP_PKEY *d2i_PKCS8PrivateKey_fp(FILE *fp, EVP_PKEY **x, pem_password_cb *cb, void *u);
```

```
int i2d_PKCS8PrivateKey_bio(BIO *bp, const EVP_PKEY *x, const EVP_CIPHER *enc,  
char *kstr, int klen,  
pem_password_cb *cb, void *u);
```

```
int i2d_PKCS8PrivateKey_fp(FILE *fp, const EVP_PKEY *x, const EVP_CIPHER *enc,  
char *kstr, int klen,  
pem_password_cb *cb, void *u);
```

```
int i2d_PKCS8PrivateKey_nid_bio(BIO *bp, const EVP_PKEY *x, int nid,
```

```
char *kstr, int klen,  
pem_password_cb *cb, void *u);
```

```
int i2d_PKCS8PrivateKey_nid_fp(FILE *fp, const EVP_PKEY *x, int nid,  
char *kstr, int klen,  
pem_password_cb *cb, void *u);
```

DESCRIPTION

The PKCS#8 functions encode and decode private keys in PKCS#8 format using both PKCS#5 v1.5 and PKCS#5 v2.0 password based encryption algorithms.

Other than the use of DER as opposed to PEM these functions are identical to the corresponding PEM function as described in PEM_read_PrivateKey(3).

NOTES

These functions are currently the only way to store encrypted private keys using DER format.

Currently all the functions use BIOs or FILE pointers, there are no functions which work directly on memory: this can be readily worked around by converting the buffers to memory BIOs, see BIO_s_mem(3) for details.

These functions make no assumption regarding the pass phrase received from the password callback. It will simply be treated as a byte sequence.

RETURN VALUES

d2i_PKCS8PrivateKey_bio() and d2i_PKCS8PrivateKey_fp() return a valid EVP_PKEY structure or NULL if an error occurred.

i2d_PKCS8PrivateKey_bio(), i2d_PKCS8PrivateKey_fp(),
i2d_PKCS8PrivateKey_nid_bio() and i2d_PKCS8PrivateKey_nid_fp() return 1
on success or 0 on error.

SEE ALSO

PEM_read_PrivateKey(3), passphrase-encoding(7)

COPYRIGHT

Copyright 2002-2018 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use
this file except in compliance with the License. You can obtain a copy
in the file LICENSE in the source distribution or at
<<https://www.openssl.org/source/license.html>>.

3.0.7 2023-07-13 D2I_PKCS8PRIVATEKEY_BIO(3ossl)