



*Full credit is given to the above companies including the OS that this PDF file was generated!*

*Red Hat Enterprise Linux Release 9.2 Manual Pages on 'ip-stats.8' command*

\$ *man ip-stats.8*

## IP-STATS(8)

## Linux

## IP-STATS(8)

NAME

ip-stats - manage and show interface statistics

## SYNOPSIS

ip stats { COMMAND | help }

```
ip stats show [ dev DEV ] [ group GROUP [ subgroup SUBGROUP [ suite  
    SUITE ] ... ] ... ] ...
```

```
ip stats set dev DEV I3 stats { on | off }
```

## DESCRIPTION

ip stats set

is used for toggling whether a certain HW statistics suite is collected on a given netdevice. The following statistics suites are supported:

L3\_stats L3 stats reflect traffic that takes place in a HW de?

vice on an object that corresponds to the given software  
netdevice.

ip stats show

is used for showing stats on a given netdevice, or dumping statistics across all netdevices. By default, all stats are requested. It is possible to filter which stats are requested by using the group and subgroup keywords.

It is possible to specify several groups, or several subgroups for one group. When no subgroups are given for a group, all the

subgroups are requested.

The following groups are recognized:

group link - Link statistics. The same suite that "ip -s link show" shows.

group offload - A group that contains a number of HW-oriented statistics. See below for individual subgroups within this group.

group xstats - Extended statistics. A subgroup identifies the type of netdevice to show the statistics for.

group xstats\_slave - Extended statistics for the slave of a net? device of a given type. A subgroup identifies the type of master netdevice.

group afstats - A group for address-family specific netdevice statistics.

group offload subgroups:

subgroup cpu\_hit - The cpu\_hit statistics suite is useful on hardware netdevices. The link statistics on these devices reflect both the hardware- and software-datapath traffic.

The cpu\_hit statistics then only reflect software-data? path traffic.

subgroup hw\_stats\_info - This suite does not include traffic statistics, but rather communicates the state of other statistics. Through this subgroup, it is possible to dis? cover whether a given statistic was enabled, and when it was, whether any device driver actually configured its device to collect these statistics. For example, l3\_stats was enabled in the following case, but no driver has in? stalled it:

```
# ip stats show dev swp1 group offload subgroup
```

```
hw_stats_info
```

```
56: swp1: group offload subgroup hw_stats_info
```

```
l3_stats on used off
```

After an L3 address is added to the netdevice, the

counter will be installed:

```
# ip addr add dev swp1 192.0.2.1/28
# ip stats show dev swp1 group offload subgroup
hw_stats_info
56: swp1: group offload subgroup hw_stats_info
    I3_stats on used on
```

subgroup I3\_stats - These statistics reflect L3 traffic that

takes place in HW on an object that corresponds to the netdevice. Note that this suite is disabled by default and needs to be first enabled through ip stats set.

For example:

```
# ip stats show dev swp2.200 group offload subgroup
I3_stats
112: swp2.200: group offload subgroup I3_stats on used on
    RX: bytes packets errors dropped  mcast
        8900    72    2    0    3
    TX: bytes packets errors dropped
        7176    58    0    0
```

Note how the I3\_stats\_info for the selected group is also part of the dump.

group xstats and group xstats\_slave subgroups:

subgroup bridge [ suite stp ] [ suite mcast ] - Statistics for STP and, respectively, IGMP / MLD (under the keyword mcast) traffic on bridges and their slaves.

subgroup bond [ suite 802.3ad ] - Statistics for LACP traffic on bond devices and their slaves.

group afstats subgroups:

subgroup mpls - Statistics for MPLS traffic seen on the netdevice. For example:

```
# ip stats show dev veth01 group afstats subgroup mpls
3: veth01: group afstats subgroup mpls
    RX: bytes packets errors dropped noroute
        0    0    0    0    0
```

TX: bytes packets errors dropped

216 2 0 0

## EXAMPLES

```
# ip stats set dev swp1 l3_stats on
```

Enables collection of L3 HW statistics on swp1.

```
# ip stats show group offload
```

Shows all offload statistics on all netdevices.

```
# ip stats show dev swp1 group link
```

Shows link statistics on the given netdevice.

## SEE ALSO

ip(8), ip-link(8),

## AUTHOR

Manpage by Petr Machata.

iproute2

16 Mar 2022

IP-STATS(8)