



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'islessequal.3p' command

\$ man islessequal.3p

ISLESSEQUAL(3P) POSIX Programmer's Manual ISLESSEQUAL(3P)

PROLOG

This manual page is part of the POSIX Programmer's Manual. The Linux implementation of this interface may differ (consult the corresponding Linux manual page for details of Linux behavior), or the interface may not be implemented on Linux.

NAME

islessequal ? test if x is less than or equal to y

SYNOPSIS

```
#include <math.h>

int islessequal(real-floating x, real-floating y);
```

DESCRIPTION

The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of POSIX.1?2017 defers to the ISO C standard.

The `islessequal()` macro shall determine whether its first argument is less than or equal to its second argument. The value of `islessequal(x, y)` shall be equal to `(x <= (y))`; however, unlike `(x <= (y))`, `islessequal(x, y)` shall not raise the invalid floating-point exception when `x` and `y` are unordered.

RETURN VALUE

Upon successful completion, the `islessequal()` macro shall return the

value of $(x) \leq (y)$.

If x or y is NaN, 0 shall be returned.

ERRORS

No errors are defined.

The following sections are informative.

EXAMPLES

None.

APPLICATION USAGE

The relational and equality operators support the usual mathematical relationships between numeric values. For any ordered pair of numeric values, exactly one of the relationships (less, greater, and equal) is true. Relational operators may raise the invalid floating-point exception when argument values are NaNs. For a NaN and a numeric value, or for two NaNs, just the unordered relationship is true. This macro is a quiet (non-floating-point exception raising) version of a relational operator. It facilitates writing efficient code that accounts for NaNs without suffering the invalid floating-point exception. In the SYNOPSIS section, `real-floating` indicates that the argument shall be an expression of real-floating type.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

`isgreater()`, `isgreaterequal()`, `isless()`, `islessgreater()`, `isunordered()`

The Base Definitions volume of POSIX.1-2017, `<math.h>`

COPYRIGHT

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1-2017, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 7, 2018 Edition, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and

The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html> .

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see https://www.kernel.org/doc/man-pages/reporting_bugs.html .

IEEE/The Open Group

2017

ISLESSEQUAL(3P)