



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'lpc-cups.8' command**

**\$ man lpc-cups.8**

lpc(8) Apple Inc. lpc(8)

### **NAME**

lpc - line printer control program (deprecated)

### **SYNOPSIS**

lpc [ command [ parameter(s) ] ]

### **DESCRIPTION**

lpc provides limited control over printer and class queues provided by

CUPS. It can also be used to query the state of queues.

If no command is specified on the command-line, lpc displays a prompt

and accepts commands from the standard input.

### **COMMANDS**

The lpc program accepts a subset of commands accepted by the Berkeley

lpc program of the same name:

exit Exits the command interpreter.

help [command]

? [command]

Displays a short help message.

quit Exits the command interpreter.

status [queue]

Displays the status of one or more printer or class queues.

### **NOTES**

This program is deprecated and will be removed in a future feature re?

lease of CUPS.

Since `lpc` is geared towards the Berkeley printing system, it is impossible to use `lpc` to configure printer or class queues provided by CUPS. To configure printer or class queues you must use the `lpadmin(8)` command or another CUPS-compatible client with that functionality.

#### SEE ALSO

`cancel(1)`, `cupsaccept(8)`, `cupsenable(8)`, `lp(1)`, `lpadmin(8)`, `lpr(1)`, `lprm(1)`, `lpstat(1)`, CUPS Online Help (<http://localhost:631/help>)

#### COPYRIGHT

Copyright ? 2007-2019 by Apple Inc.

26 April 2019

CUPS

`lpc(8)`