



## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'mkfifo.1' command***

**\$ man mkfifo.1**

MKFIFO(1) User Commands MKFIFO(1)

### NAME

mkfifo - make FIFOs (named pipes)

### SYNOPSIS

mkfifo [OPTION]... NAME...

### DESCRIPTION

Create named pipes (FIFOs) with the given NAMES.

Mandatory arguments to long options are mandatory for short options too.

-m, --mode=MODE

set file permission bits to MODE, not a=rw - umask

-Z set the SELinux security context to default type

--context[=CTX]

like -Z, or if CTX is specified then set the SELinux or SMACK security context to CTX

--help display this help and exit

--version

output version information and exit

### AUTHOR

Written by David MacKenzie.

### REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

## COPYRIGHT

Copyright ? 2020 Free Software Foundation, Inc. License GPLv3+: GNU

GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

## SEE ALSO

mkfifo(3)

Full documentation <<https://www.gnu.org/software/coreutils/mkfifo>>

or available locally via: info '(coreutils) mkfifo invocation'

GNU coreutils 8.32

January 2023

MKFIFO(1)