



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'modprobe.8' command

\$ man modprobe.8

MODPROBE(8) modprobe MODPROBE(8)

NAME

modprobe - Add and remove modules from the Linux Kernel

SYNOPSIS

modprobe [-v] [-V] [-C config-file] [-n] [-i] [-q] [-b] [modulename]

[module parameters...]

modprobe [-r] [-v] [-n] [-i] [modulename...]

modprobe [-c]

modprobe [--dump-modversions] [filename]

DESCRIPTION

modprobe intelligently adds or removes a module from the Linux kernel:

note that for convenience, there is no difference between _ and - in

module names (automatic underscore conversion is performed). modprobe

looks in the module directory /lib/modules/`uname -r` for all the

modules and other files, except for the optional configuration files in

the /etc/modprobe.d directory (see modprobe.d(5)). modprobe will also

use module options specified on the kernel command line in the form of

<module>.<option> and blacklists in the form of

modprobe.blacklist=<module>.

Note that unlike in 2.4 series Linux kernels (which are not supported

by this tool) this version of modprobe does not do anything to the

module itself: the work of resolving symbols and understanding

parameters is done inside the kernel. So module failure is sometimes

accompanied by a kernel message: see dmesg(8).

modprobe expects an up-to-date modules.dep.bin file as generated by the corresponding depmod utility shipped along with modprobe (see depmod(8)). This file lists what other modules each module needs (if any), and modprobe uses this to add or remove these dependencies automatically.

If any arguments are given after the modulename, they are passed to the kernel (in addition to any options listed in the configuration file).

OPTIONS

-a, --all

Insert all module names on the command line.

-b, --use-blacklist

This option causes modprobe to apply the blacklist commands in the configuration files (if any) to module names as well. It is usually used by udev(7).

-C, --config

This option overrides the default configuration directory (/etc/modprobe.d).

This option is passed through install or remove commands to other modprobe commands in the MODPROBE_OPTIONS environment variable.

-c, --showconfig

Dump out the effective configuration from the config directory and exit.

--dump-modversions

Print out a list of module versioning information required by a module. This option is commonly used by distributions in order to package up a Linux kernel module using module versioning deps.

-d, --dirname

Root directory for modules, / by default.

--first-time

Normally, modprobe will succeed (and do nothing) if told to insert a module which is already present or to remove a module which isn't present. This is ideal for simple scripts; however, more

complicated scripts often want to know whether modprobe really did something: this option makes modprobe fail in the case that it actually didn't do anything.

--force-vermagic

Every module contains a small string containing important information, such as the kernel and compiler versions. If a module fails to load and the kernel complains that the "version magic" doesn't match, you can use this option to remove it. Naturally, this check is there for your protection, so using this option is dangerous unless you know what you're doing.

This applies to any modules inserted: both the module (or alias) on the command line and any modules on which it depends.

--force-modversion

When modules are compiled with CONFIG_MODVERSIONS set, a section detailing the versions of every interface used by (or supplied by) the module is created. If a module fails to load and the kernel complains that the module disagrees about a version of some interface, you can use "--force-modversion" to remove the version information altogether. Naturally, this check is there for your protection, so using this option is dangerous unless you know what you're doing.

This applies to any modules inserted: both the module (or alias) on the command line and any modules on which it depends.

-f, --force

Try to strip any versioning information from the module which might otherwise stop it from loading: this is the same as using both --force-vermagic and --force-modversion. Naturally, these checks are there for your protection, so using this option is dangerous unless you know what you are doing.

This applies to any modules inserted: both the module (or alias) on the command line and any modules on which it depends.

-i, --ignore-install, --ignore-remove

This option causes modprobe to ignore install and remove commands

in the configuration file (if any) for the module specified on the command line (any dependent modules are still subject to commands set for them in the configuration file). Both install and remove commands will currently be ignored when this option is used regardless of whether the request was more specifically made with only one or other (and not both) of --ignore-install or --ignore-remove. See modprobe.d(5).

-n, --dry-run, --show

This option does everything but actually insert or delete the modules (or run the install or remove commands). Combined with -v, it is useful for debugging problems. For historical reasons both --dry-run and --show actually mean the same thing and are interchangeable.

-q, --quiet

With this flag, modprobe won't print an error message if you try to remove or insert a module it can't find (and isn't an alias or install/remove command). However, it will still return with a non-zero exit status. The kernel uses this to opportunistically probe for modules which might exist using request_module.

-R, --resolve-alias

Print all module names matching an alias. This can be useful for debugging module alias problems.

-r, --remove

This option causes modprobe to remove rather than insert a module. If the modules it depends on are also unused, modprobe will try to remove them too. Unlike insertion, more than one module can be specified on the command line (it does not make sense to specify module parameters when removing modules).

There is usually no reason to remove modules, but some buggy modules require it. Your distribution kernel may not have been built to support removal of modules at all.

-S, --set-version

Set the kernel version, rather than using uname(2) to decide on the

kernel version (which dictates where to find the modules).

--show-depends

List the dependencies of a module (or alias), including the module itself. This produces a (possibly empty) set of module filenames, one per line, each starting with "insmod" and is typically used by distributions to determine which modules to include when generating initrd/initramfs images. Install commands which apply are shown prefixed by "install". It does not run any of the install commands.

Note that modinfo(8) can be used to extract dependencies of a module from the module itself, but knows nothing of aliases or install commands.

-s, --syslog

This option causes any error messages to go through the syslog mechanism (as LOG_DAEMON with level LOG_NOTICE) rather than to standard error. This is also automatically enabled when stderr is unavailable.

This option is passed through install or remove commands to other modprobe commands in the MODPROBE_OPTIONS environment variable.

-V, --version

Show version of program and exit.

-v, --verbose

Print messages about what the program is doing. Usually modprobe only prints messages if something goes wrong.

This option is passed through install or remove commands to other modprobe commands in the MODPROBE_OPTIONS environment variable.

ENVIRONMENT

The MODPROBE_OPTIONS environment variable can also be used to pass arguments to modprobe.

COPYRIGHT

This manual page originally Copyright 2002, Rusty Russell, IBM Corporation. Maintained by Jon Masters and others.

SEE ALSO

modprobe.d(5), insmod(8), rmmod(8), lsmod(8), modinfo(8) depmod(8)

AUTHORS

Jon Masters <jcm@jonmasters.org>

Developer

Robby Workman <rworkman@slackware.com>

Developer

Lucas De Marchi <lucas.de.marchi@gmail.com>

Developer

kmmod

12/27/2020

MODPROBE(8)