



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'mq_timedsend.3' command

\$ man mq_timedsend.3

MQ_SEND(3) Linux Programmer's Manual MQ_SEND(3)

NAME

mq_send, mq_timedsend - send a message to a message queue

SYNOPSIS

```
#include <mqueue.h>

int mq_send(mqd_t mqdes, const char *msg_ptr,
            size_t msg_len, unsigned int msg_prio);

#include <time.h>

#include <mqueue.h>

int mq_timedsend(mqd_t mqdes, const char *msg_ptr,
                size_t msg_len, unsigned int msg_prio,
                const struct timespec *abs_timeout);
```

Link with -lrt.

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
mq_timedsend():
    _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

mq_send() adds the message pointed to by msg_ptr to the message queue referred to by the message queue descriptor mqdes. The msg_len argument specifies the length of the message pointed to by msg_ptr; this length must be less than or equal to the queue's mq_msgsize attribute. Zero-length messages are allowed.

The msg_prio argument is a nonnegative integer that specifies the pri?

ority of this message. Messages are placed on the queue in decreasing order of priority, with newer messages of the same priority being placed after older messages with the same priority. See `mq_overview(7)` for details on the range for the message priority.

If the message queue is already full (i.e., the number of messages on the queue equals the queue's `mq_maxmsg` attribute), then, by default, `mq_send()` blocks until sufficient space becomes available to allow the message to be queued, or until the call is interrupted by a signal handler. If the `O_NONBLOCK` flag is enabled for the message queue description, then the call instead fails immediately with the error `EAGAIN`.

`mq_timedsend()` behaves just like `mq_send()`, except that if the queue is full and the `O_NONBLOCK` flag is not enabled for the message queue description, then `abs_timeout` points to a structure which specifies how long the call will block. This value is an absolute timeout in seconds and nanoseconds since the Epoch, 1970-01-01 00:00:00 +0000 (UTC), specified in the following structure:

```
struct timespec {
    time_t tv_sec;    /* seconds */
    long tv_nsec;    /* nanoseconds */
};
```

If the message queue is full, and the timeout has already expired by the time of the call, `mq_timedsend()` returns immediately.

RETURN VALUE

On success, `mq_send()` and `mq_timedsend()` return zero; on error, `-1` is returned, with `errno` set to indicate the error.

ERRORS

EAGAIN The queue was full, and the `O_NONBLOCK` flag was set for the message queue description referred to by `mqdes`.

EBADF The descriptor specified in `mqdes` was invalid or not opened for writing.

EINTR The call was interrupted by a signal handler; see `signal(7)`.

EINVAL The call would have blocked, and `abs_timeout` was invalid, either because `tv_sec` was less than zero, or because `tv_nsec` was less

than zero or greater than 1000 million.

EMSGSIZE

msg_len was greater than the mq_msgsize attribute of the message queue.

ETIMEDOUT

The call timed out before a message could be transferred.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?mq_send(), mq_timedsend() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

NOTES

On Linux, mq_timedsend() is a system call, and mq_send() is a library function layered on top of that system call.

SEE ALSO

mq_close(3), mq_getattr(3), mq_notify(3), mq_open(3), mq_receive(3),
mq_unlink(3), mq_overview(7), time(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.