



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'mq_timedsend.3p' command

\$ man mq_timedsend.3p

MQ_TIMEDSEND(3P) POSIX Programmer's Manual MQ_TIMEDSEND(3P)

PROLOG

This manual page is part of the POSIX Programmer's Manual. The Linux implementation of this interface may differ (consult the corresponding Linux manual page for details of Linux behavior), or the interface may not be implemented on Linux.

NAME

mq_timedsend ? send a message to a message queue (ADVANCED REALTIME)

SYNOPSIS

```
#include <mqueue.h>

#include <time.h>

int mq_timedsend(mqd_t mqdes, const char *msg_ptr, size_t msg_len,
    unsigned msg_prio, const struct timespec *abstime);
```

DESCRIPTION

Refer to mq_send().

COPYRIGHT

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1-2017, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 7, 2018 Edition, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard

is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html> .

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see https://www.kernel.org/doc/man-pages/reporting_bugs.html .

IEEE/The Open Group

2017

MQ_TIMEDSEND(3P)