



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'npm-exec.1' command

\$ man npm-exec.1

NPM-EXEC(1)

NPM-EXEC(1)

NAME

npm-exec - Run a command from a local or remote npm package

Synopsis

npm exec -- <pkg>[@<version>] [args...]

npm exec --package=<pkg>[@<version>] -- <cmd> [args...]

npm exec -c '<cmd> [args...]'

npm exec --package=foo -c '<cmd> [args...]'

alias: x

Description

This command allows you to run an arbitrary command from an npm package

(either one installed locally, or fetched remotely), in a similar con?

text as running it via npm run.

Run without positional arguments or --call, this allows you to interac?

tively run commands in the same sort of shell environment that pack?

age.json scripts are run. Interactive mode is not supported in CI en?

vironments when standard input is a TTY, to prevent hangs.

Whatever packages are specified by the --package option will be pro?

vided in the PATH of the executed command, along with any locally in?

stalled package executables. The --package option may be specified

multiple times, to execute the supplied command in an environment where

all specified packages are available.

If any requested packages are not present in the local project depen?

dencies, then they are installed to a folder in the npm cache, which is added to the PATH environment variable in the executed process. A prompt is printed (which can be suppressed by providing either --yes or --no).

Package names provided without a specifier will be matched with what? ever version exists in the local project. Package names with a specifier will only be considered a match if they have the exact same name and version as the local dependency.

If no -c or --call option is provided, then the positional arguments are used to generate the command string. If no --package options are provided, then npm will attempt to determine the executable name from the package specifier provided as the first positional argument according to the following heuristic:

- ? If the package has a single entry in its bin field in package.json, or if all entries are aliases of the same command, then that command will be used.

- ? If the package has multiple bin entries, and one of them matches the unscoped portion of the name field, then that command will be used.

- ? If this does not result in exactly one option (either because there are no bin entries, or none of them match the name of the package), then npm exec exits with an error.

To run a binary other than the named binary, specify one or more --package options, which will prevent npm from inferring the package from the first command argument.

npx vs npm exec

When run via the npx binary, all flags and options must be set prior to any positional arguments. When run via npm exec, a double-hyphen -- flag can be used to suppress npm's parsing of switches and options that should be sent to the executed command.

For example:

```
$ npx foo@latest bar --package=@npmcli/foo
```

In this case, npm will resolve the foo package name, and run the following command:

```
$ foo bar --package=@npmcli/foo
```

Since the --package option comes after the positional arguments, it is treated as an argument to the executed command.

In contrast, due to npm's argument parsing logic, running this command is different:

```
$ npm exec foo@latest bar --package=@npmcli/foo
```

In this case, npm will parse the --package option first, resolving the @npmcli/foo package. Then, it will execute the following command in that context:

```
$ foo@latest bar
```

The double-hyphen character is recommended to explicitly tell npm to stop parsing command line options and switches. The following command would thus be equivalent to the npx command above:

```
$ npm exec -- foo@latest bar --package=@npmcli/foo
```

Configuration

package

? Default:

? Type: String (can be set multiple times)

The package or packages to install for npm help exec

call

? Default: ""

? Type: String

Optional companion option for npm exec, npx that allows for specifying a custom command to be run along with the installed packages.

```
npm exec --package yo --package generator-node --call "yo node"
```

workspace

? Default:

? Type: String (can be set multiple times)

Enable running a command in the context of the configured workspaces of the current project while filtering by running only the workspaces defined by this configuration option.

Valid values for the workspace config are either:

? Workspace names

? Path to a workspace directory

? Path to a parent workspace directory (will result in selecting all workspaces within that folder)

When set for the npm init command, this may be set to the folder of a workspace which does not yet exist, to create the folder and set it up as a brand new workspace within the project.

This value is not exported to the environment for child processes.

workspaces

? Default: null

? Type: null or Boolean

Set to true to run the command in the context of all configured workspaces.

Explicitly setting this to false will cause commands like install to ignore workspaces altogether. When not set explicitly:

? Commands that operate on the node_modules tree (install, update, etc.) will link workspaces into the node_modules folder. - Commands that do other things (test, exec, publish, etc.) will operate on the root project, unless one or more workspaces are specified in the workspace config.

This value is not exported to the environment for child processes.

include-workspace-root

? Default: false

? Type: Boolean

Include the workspace root when workspaces are enabled for a command.

When false, specifying individual workspaces via the workspace config, or all workspaces via the workspaces flag, will cause npm to operate only on the specified workspaces, and not on the root project.

This value is not exported to the environment for child processes.

Examples

Run the version of tap in the local dependencies, with the provided arguments:

```
$ npm exec -- tap --bail test/foo.js
```

```
$ npx tap --bail test/foo.js
```

Run a command other than the command whose name matches the package name by specifying a --package option:

```
$ npm exec --package=foo -- bar --bar-argument
```

~ or ~

```
$ npx --package=foo bar --bar-argument
```

Run an arbitrary shell script, in the context of the current project:

```
$ npm x -c 'eslint && say "hooray, lint passed"'
```

```
$ npx -c 'eslint && say "hooray, lint passed"'
```

Workspaces support

You may use the workspace or workspaces configs in order to run an arbitrary command from an npm package (either one installed locally, or fetched remotely) in the context of the specified workspaces. If no positional argument or --call option is provided, it will open an interactive subshell in the context of each of these configured workspaces one at a time.

Given a project with configured workspaces, e.g:

```
.
+-- package.json
`-- packages
  +-- a
  | `-- package.json
  +-- b
  | `-- package.json
  `-- c
    `-- package.json
```

Assuming the workspace configuration is properly set up at the root

level package.json file. e.g:

```
{  
  "workspaces": [ "./packages/*" ]  
}
```

You can execute an arbitrary command from a package in the context of each of the configured workspaces when using the workspaces configuration options, in this example we're using eslint to lint any js file

found within each workspace folder:

```
npm exec --ws -- eslint /*.js
```

Filtering workspaces

It's also possible to execute a command in a single workspace using the workspace config along with a name or directory path:

```
npm exec --workspace=a -- eslint /*.js
```

The workspace config can also be specified multiple times in order to run a specific script in the context of multiple workspaces. When defining values for the workspace config in the command line, it is also possible to use -w as a shorthand, e.g.:

```
npm exec -w a -w b -- eslint /*.js
```

This last command will run the eslint command in both ./packages/a and ./packages/b folders.

Compatibility with Older npx Versions

The npx binary was rewritten in npm v7.0.0, and the standalone npx package deprecated at that time. npx uses the npm exec command instead of a separate argument parser and install process, with some affordances to maintain backwards compatibility with the arguments it accepted in previous versions.

This resulted in some shifts in its functionality:

- ? Any npm config value may be provided.
- ? To prevent security and user-experience problems from mistyping package names, npx prompts before installing anything. Suppress this prompt with the -y or --yes option.
- ? The --no-install option is deprecated, and will be converted to --no.
- ? Shell fallback functionality is removed, as it is not advisable.
- ? The -p argument is a shorthand for --parseable in npm, but shorthand for --package in npx. This is maintained, but only for the npx executable.
- ? The --ignore-existing option is removed. Locally installed bins are always present in the executed process PATH.
- ? The --npm option is removed. npx will always use the npm it ships with.

- ? The --node-arg and -n options are removed.
- ? The --always-spawn option is redundant, and thus removed.
- ? The --shell option is replaced with --script-shell, but maintained in the npx executable for backwards compatibility.

A note on caching

The npm cli utilizes its internal package cache when using the package name specified. You can use the following to change how and when the cli uses this cache. See npm help cache for more on how the cache works.

prefer-online

Forces staleness checks for packages, making the cli look for updates immediately even if the package is already in the cache.

prefer-offline

Bypasses staleness checks for packages. Missing data will still be requested from the server. To force full offline mode, use offline.

offline

Forces full offline mode. Any packages not locally cached will result in an error.

workspace

? Default:

? Type: String (can be set multiple times)

Enable running a command in the context of the configured workspaces of the current project while filtering by running only the workspaces defined by this configuration option.

Valid values for the workspace config are either:

? Workspace names

? Path to a workspace directory

? Path to a parent workspace directory (will result to selecting all of the nested workspaces)

This value is not exported to the environment for child processes.

workspaces

? Alias: --ws

? Type: Boolean

? Default: false

Run scripts in the context of all configured workspaces for the current project.

See Also

? npm help run-script

? npm help scripts

? npm help test

? npm help start

? npm help restart

? npm help stop

? npm help config

? npm help workspaces

? npm help npx

February 2023

NPM-EXEC(1)