



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'npm-token.1' command**

**\$ man npm-token.1**

NPM-TOKEN(1)

NPM-TOKEN(1)

### NAME

npm-token - Manage your authentication tokens

### Synopsis

npm token list

npm token revoke <id|token>

npm token create [--read-only] [--cidr=list]

Note: This command is unaware of workspaces.

### Description

This lets you list, create and revoke authentication tokens.

? npm token list: Shows a table of all active authentication tokens.

You can request this as JSON with --json or tab-separated values with

--parseable.

id	token	created	read-only	CIDR whitelist
7f3134	1fa9ba?	2017-10-02	yes	
c03241	af7aef?	2017-10-02	no	192.168.0.1/24
e0cf92	3a436a?	2017-10-02	no	
63eb9d	74ef35?	2017-09-28	no	

2daaa8	cbad5f?	2017-09-26	no		
68c2fe	127e51?	2017-09-23	no		
6334e1	1dadd1?	2017-09-23	no		

? npm token create [--read-only] [--cidr=<cidr-ranges>]: Create a new authentication token. It can be --read-only, or accept a list of CIDR [https://en.wikipedia.org/wiki/Classless\\_Inter-Domain\\_Routing](https://en.wikipedia.org/wiki/Classless_Inter-Domain_Routing) ranges with which to limit use of this token. This will prompt you for your password, and, if you have two-factor authentication enabled, an otp. Currently, the cli can not generate automation tokens. Please refer to the docs website <https://docs.npmjs.com/creating-and-viewing-access-tokens> for more information on generating automation tokens.

token	a73c9572-f1b9-8983-983d-ba3ac3cc913d	
cidr_whitelist		
readonly	false	
created	2017-10-02T07:52:24.838Z	

? npm token revoke <token|id>: Immediately removes an authentication token from the registry. You will no longer be able to use it. This can accept both complete tokens (such as those you get back from npm token create, and those found in your .npmrc), and ids as seen in the parseable or json output of npm token list. This will NOT accept the truncated token found in the normal npm token list output.

## Configuration

### read-only

? Default: false

? Type: Boolean

This is used to mark a token as unable to publish when configuring limited access tokens with the npm token create command.

cidr

? Default: null

? Type: null or String (can be set multiple times)

This is a list of CIDR address to be used when configuring limited access tokens with the npm token create command.

registry

? Default: "https://registry.npmjs.org/"

? Type: URL

The base URL of the npm registry.

otp

? Default: null

? Type: null or String

This is a one-time password from a two-factor authenticator. It's needed when publishing or changing package permissions with npm access. If not set, and a registry response fails with a challenge for a one-time password, npm will prompt on the command line for one.

See Also

? npm help adduser

? npm help registry

? npm help config

? npm help npmrc

? npm help owner

? npm help whoami

? npm help profile