



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'nvme-fid-support-effects-log.1' command

\$ man nvme-fid-support-effects-log.1

NVME-FID-SUPPORT-(1) NVMe Manual NVME-FID-SUPPORT-(1)

NAME

nvme-fid-support-effects-log - Send NVMe FID Support and Effects log,
return result and structure

SYNOPSIS

nvme fid-support-effects-log <device> [-o <fmt> | --output-format=<fmt>]

DESCRIPTION

For the NVMe device given, sends an FID Support and Effects log and
provides the result and returned log structure.

The <device> parameter is mandatory and may be either the NVMe
character device (ex: /dev/nvme0), or a namespace block device (ex:
/dev/nvme0n1).

On success, the structure may be returned in one of several ways
depending on the option flags; the structure may be parsed by the
program or the raw buffer may be printed to stdout.

OPTIONS

-o <format>, --output-format=<format>

Set the reporting format to normal, json, or binary. Only one
output format can be used at a time.

-H, --human-readable

This option will parse and format many of the bit fields into
human-readable formats.

EXAMPLES

No examples yet.

NVME

Part of the nvme-user suite

NVMe	06/23/2023	NVME-FID-SUPPORT-(1)
------	------------	----------------------