



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'openssl-verify.1oss1' command

\$ man openssl-verify.1oss1

OPENSSL-VERIFY(1oss1) OpenSSL OPENSSL-VERIFY(1oss1)

NAME

openssl-verify - certificate verification command

SYNOPSIS

```
openssl verify [-help] [-CRLfile filename|uri] [-crl_download]
[-show_chain] [-verbose] [-trusted filename|uri] [-untrusted
filename|uri] [-vfyopt nm:v] [-nameopt option] [-CAfile file]
[-no-CAfile] [-CApath dir] [-no-CApath] [-CAstore uri] [-no-CAstore]
[-engine id] [-allow_proxy_certs] [-attime timestamp] [-no_check_time]
[-check_ss_sig] [-crl_check] [-crl_check_all] [-explicit_policy]
[-extended_crl] [-ignore_critical] [-inhibit_any] [-inhibit_map]
[-partial_chain] [-policy arg] [-policy_check] [-policy_print]
[-purpose purpose] [-suiteB_128] [-suiteB_128_only] [-suiteB_192]
[-trusted_first] [-no_alt_chains] [-use_deltas] [-auth_level num]
[-verify_depth num] [-verify_email email] [-verify_hostname hostname]
[-verify_ip ip] [-verify_name name] [-x509_strict] [-issuer_checks]
[-provider name] [-provider-path path] [-propquery propq] [--]
[certificate ...]
```

DESCRIPTION

This command verifies certificate chains. If a certificate chain has multiple problems, this program attempts to display all of them.

OPTIONS

-help

Print out a usage message.

`-CRLfile filename|uri`

The file or URI should contain one or more CRLs in PEM or DER format. This option can be specified more than once to include CRLs from multiple sources.

`-crl_download`

Attempt to download CRL information for certificates via their CDP entries.

`-show_chain`

Display information about the certificate chain that has been built (if successful). Certificates in the chain that came from the untrusted list will be flagged as "untrusted".

`-verbose`

Print extra information about the operations being performed.

`-trusted filename|uri`

A file or URI of (more or less) trusted certificates. See `openssl-verification-options(1)` for more information on trust settings.

This option can be specified more than once to load certificates from multiple sources.

`-untrusted filename|uri`

A file or URI of untrusted certificates to use for chain building.

This option can be specified more than once to load certificates from multiple sources.

`-vfyopt nm:v`

Pass options to the signature algorithm during verify operations.

Names and values of these options are algorithm-specific.

`-nameopt option`

This specifies how the subject or issuer names are displayed. See `openssl-namedisplay-options(1)` for details.

`-engine id`

See "Engine Options" in `openssl(1)`. This option is deprecated.

To load certificates or CRLs that require engine support, specify

the -engine option before any of the -trusted, -untrusted or -CRLfile options.

-CAfile file, -no-CAfile, -CApath dir, -no-CApath, -CAstore uri, -no-CAstore

See "Trusted Certificate Options" in openssl-verification-options(1) for details.

-allow_proxy_certs, -atime, -no_check_time, -check_ss_sig, -crl_check, -crl_check_all, -explicit_policy, -extended_crl, -ignore_critical, -inhibit_any, -inhibit_map, -no_alt_chains, -partial_chain, -policy, -policy_check, -policy_print, -purpose, -suiteB_128, -suiteB_128_only, -suiteB_192, -trusted_first, -use_deltas, -auth_level, -verify_depth, -verify_email, -verify_hostname, -verify_ip, -verify_name, -x509_strict -issuer_checks

Set various options of certificate chain verification. See "Verification Options" in openssl-verification-options(1) for details.

-provider name
-provider-path path
-propquery propq

See "Provider Options" in openssl(1), provider(7), and property(7).

-- Indicates the last option. All arguments following this are assumed to be certificate files. This is useful if the first certificate filename begins with a -.

certificate ...

One or more target certificates to verify, one per file. If no certificates are given, this command will attempt to read a single certificate from standard input.

DIAGNOSTICS

When a verify operation fails the output messages can be somewhat cryptic. The general form of the error message is:

```
server.pem: /C=AU/ST=Queensland/O=CryptSoft Pty Ltd/CN=Test CA (1024 bit)
error 24 at 1 depth lookup:invalid CA certificate
```

The first line contains the name of the certificate being verified

followed by the subject name of the certificate. The second line contains the error number and the depth. The depth is number of the certificate being verified when a problem was detected starting with zero for the target ("leaf") certificate itself then 1 for the CA that signed the target certificate and so on. Finally a textual version of the error number is presented.

A list of the error codes and messages can be found in `X509_STORE_CTX_get_error(3)`; the full list is defined in the header file `<openssl/x509_vfy.h>`.

This command ignores many errors, in order to allow all the problems with a certificate chain to be determined.

SEE ALSO

`openssl-verification-options(1)`, `openssl-x509(1)`, `ossl_store-file(7)`

HISTORY

The `-show_chain` option was added in OpenSSL 1.1.0.

The `-engine` option was deprecated in OpenSSL 3.0.

COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use

this file except in compliance with the License. You can obtain a copy

in the file LICENSE in the source distribution or at

`<https://www.openssl.org/source/license.html>`.

3.0.7 2023-07-13 OPENSSSL-VERIFY(1ossl)