



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'openssl_user_macros.7oss1' command

\$ man openssl_user_macros.7oss1

OPENSSL_USER_MACROS(7oss1) OpenSSL OPENSSL_USER_MACROS(7oss1)

NAME

openssl_user_macros, OPENSSL_API_COMPAT, OPENSSL_NO_DEPRECATED - User defined macros

DESCRIPTION

User defined macros allow the programmer to control certain aspects of what is exposed by the OpenSSL headers.

NOTE: to be effective, a user defined macro must be defined before including any header file that depends on it, either in the compilation command ("cc -DMACRO=value") or by defining the macro in source before including any headers.

Other manual pages may refer to this page when declarations depend on user defined macros.

The macros

OPENSSL_API_COMPAT

The value is a version number, given in one of the following two forms:

"0xMNNFF000L"

This is the form supported for all versions up to 1.1.x, where "M" represents the major number, "NN" represents the minor number, and "FF" represents the fix number, as a hexadecimal number. For version 1.1.0, that's "0x10100000L".

Any version number may be given, but these numbers are the

current known major deprecation points, making them the most meaningful:

"0x00908000L" (version 0.9.8)

"0x10000000L" (version 1.0.0)

"0x10100000L" (version 1.1.0)

For convenience, higher numbers are accepted as well, as long as feasible. For example, "0x60000000L" will work as expected.

However, it is recommended to start using the second form instead:

"mmnpp"

This form is a simple decimal number calculated with this formula:

$\text{major} * 10000 + \text{minor} * 100 + \text{patch}$

where major, minor and patch are the desired major, minor and patch components of the version number. For example:

30000 corresponds to version 3.0.0

10002 corresponds to version 1.0.2

420101 corresponds to version 42.1.1

If `OPENSSL_API_COMPAT` is undefined, this default value is used in its place: 30000

`OPENSSL_NO_DEPRECATED`

If this macro is defined, all deprecated public symbols in all OpenSSL versions up to and including the version given by `OPENSSL_API_COMPAT` (or the default value given above, when `OPENSSL_API_COMPAT` isn't defined) will be hidden.

COPYRIGHT

Copyright 2018-2021 The OpenSSL Project Authors. All Rights Reserved.
Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.