



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'pdftohtml.1' command

\$ man pdftohtml.1

PDFTOHTML(1) General Commands Manual PDFTOHTML(1)

NAME

pdftohtml - program to convert PDF files into HTML, XML and PNG images

SYNOPSIS

pdftohtml [options] <PDF-file> [<HTML-file> <XML-file>]

DESCRIPTION

This manual page documents briefly the pdftohtml command. This manual page was written for the Debian GNU/Linux distribution because the original program does not have a manual page.

pdftohtml is a program that converts PDF documents into HTML. It generates its output in the current working directory. If PDF-file is ?-', it reads the PDF file from stdin.

OPTIONS

A summary of options are included below.

-h, -help

Show summary of options.

-f <int>

first page to print

-l <int>

last page to print

-q do not print any messages or errors

-v print copyright and version info

-p exchange .pdf links with .html

- c generate complex output
- s generate single HTML that includes all pages
- datauris
 - use data URLs instead of external images in HTML. Not available in all platforms
- i ignore images
- noframes
 - generate no frames. Not supported in complex output mode.
- stdout
 - use standard output
- zoom <fp>
 - zoom the PDF document (default 1.5)
- xml output for XML post-processing
- noroundcoord
 - do not round coordinates (with XML output only)
- enc <string>
 - output text encoding name
- opw <string>
 - owner password (for encrypted files)
- upw <string>
 - user password (for encrypted files)
- hidden
 - force hidden text extraction
- fmt image file format for Splash output (png or jpg). If complex is selected, but -fmt is not specified, -fmt png will be assumed
- nomerge
 - do not merge paragraphs
- nodrm override document DRM settings
- wbt <fp>
 - adjust the word break threshold percent. Default is 10. Word break occurs when distance between two adjacent characters is greater than this percent of character height.
- fontfullname

outputs the font name without any substitutions.

AUTHOR

`Pdftohtml` was developed by Gueorgui Ovtcharov and Rainer Dorsch. It is based and benefits a lot from Derek Noonburg's `xpdf` package.

This manual page was written by S?ren Boll Overgaard <boll@debian.org>, for the Debian GNU/Linux system (but may be used by others).

SEE ALSO

`pdfdetach(1)`, `pdffonts(1)`, `pdfimages(1)`, `pdfinfo(1)`, `pdftocairo(1)`,
`pdftoppm(1)`, `pdftops(1)`, `pdftotext(1)` `pdfseparate(1)`, `pdffsig(1)`, `pdffu?`
`nite(1)`

PDFTOHTML(1)