



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'podman-attach.1' command

\$ man podman-attach.1

podman-attach(1) General Commands Manual podman-attach(1)

NAME

podman-attach - Attach to a running container

SYNOPSIS

podman attach [options] container

podman container attach [options] container

DESCRIPTION

podman attach attaches to a running container using the container's name or ID, to either view its ongoing output or to control it interactively.

The container can be detached from (and leave it running) using a configurable key sequence. The default sequence is `ctrl-p,ctrl-q`. Configure the keys sequence using the `--detach-keys` OPTION, or specifying it in the `containers.conf` file: see `containers.conf(5)` for more information.

OPTIONS

`--detach-keys=sequence`

Specify the key sequence for detaching a container. Format is a single character [a-Z] or one or more `ctrl-<value>` characters where `<value>` is one of: a-z, @, ^, [, , or _. Specifying "" will disable this feature.

The default is `ctrl-p,ctrl-q`.

This option can also be set in `containers.conf(5)` file.

`--latest, -l`

Instead of providing the container name or ID, use the last created container. Note: the last started container could be from other users of Podman on the host machine. (This option is not available with the remote Podman client, including Mac and Windows (excluding WSL2) machines)

--no-stdin

Do not attach STDIN. The default is false.

--sig-proxy

Proxy received signals to the container process (non-TTY mode only).

SIGCHLD, SIGSTOP, and SIGKILL are not proxied.

The default is true.

EXAMPLES

Attach to a container called "foobar".

```
$ podman attach foobar
```

Attach to the latest created container.

```
$ podman attach --latest
```

Attach to a container that start with the ID "1234".

```
$ podman attach 1234
```

Attach to a container without attaching STDIN.

```
$ podman attach --no-stdin foobar
```

SEE ALSO

[podman\(1\)](#), [podman-exec\(1\)](#), [podman-run\(1\)](#), [containers.conf\(5\)](#)

[podman-attach\(1\)](#)