



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'podman-kube.1' command

\$ man podman-kube.1

podman-kube(1) General Commands Manual podman-kube(1)

NAME

podman-kube - Play containers, pods or volumes based on a structured input file

SYNOPSIS

podman kube subcommand

DESCRIPTION

The kube command will recreate containers, pods or volumes based on the input from a structured (like YAML) file input. Containers will be automatically started.

COMMANDS

??

?Command ? Man Page ? Description ?

??

?apply ? podman-kube-apply(1) ? Apply Kubernetes ?

? ? ? YAML based on con? ?

? ? ? tainers, pods, or ?

? ? ? volumes to a Kuber? ?

? ? ? netes cluster ?

??

?down ? podman-kube-down(1) ? Remove containers ?

? ? ? and pods based on ?

? ? ? Kubernetes YAML. ?

??

?generate ? podman-kube-generate(1) ? Generate Kubernetes ?

? ? ? YAML based on con? ?

? ? ? tainers, pods or ?

? ? ? volumes. ?

??

?play ? podman-kube-play(1) ? Create containers, ?

? ? ? pods and volumes ?

? ? ? based on Kubernetes ?

? ? ? YAML. ?

??

SEE ALSO

podman(1), podman-pod(1), podman-container(1), podman-kube-play(1),
podman-kube-down(1), podman-kube-generate(1), podman-kube-apply(1)

HISTORY

December 2018, Originally compiled by Brent Baude (bbaude at redhat dot
com)

podman-kube(1)