



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'podman-secret-inspect.1' command

\$ man podman-secret-inspect.1

podman-secret-inspect(1) General Commands Manual podman-secret-inspect(1)

NAME

podman-secret-inspect - Display detailed information on one or more secrets

SYNOPSIS

podman secret inspect [options] secret [...]

DESCRIPTION

Inspects the specified secret.

By default, this renders all results in a JSON array. If a format is specified, the given template will be executed for each result. Secrets can be queried individually by providing their full name or a unique partial name.

OPTIONS

--format, -f=format

Format secret output using Go template.

??

?Placeholder ? Description ?

??

?CreatedAt ? When secret was created ?

? ? (relative timestamp, human-readable)

? ? (man-readable) ?

??

?ID ? ID of secret ?

??

? .Spec ? Details of secret ?

??

? .Spec.Driver ? Driver info ?

??

? .Spec.Driver.Name ? Driver name (string) ?

??

? .Spec.Driver.Options ... ? Driver options (map of ?

? ? driver-specific options) ?

??

? .Spec.Name ? Name of secret ?

??

? .UpdatedAt ? When secret was last up? ?

? ? dated (relative timestamp, ?

? ? human-readable) ?

??

--help

Print usage statement.

--pretty

Print inspect output in human-readable format

EXAMPLES

\$ podman secret inspect mysecret

\$ podman secret inspect --format "{{.Name}} {{.Scope}}" mysecret

SEE ALSO

podman(1), podman-secret(1)

HISTORY

January 2021, Originally compiled by Ashley Cui acui@redhat.com

[?mailto:acui@redhat.com?](mailto:acui@redhat.com)

podman-secret-inspect(1)