



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'pvcreate.8' command

\$ man pvcreate.8

PVCREATE(8) System Manager's Manual PVCREATE(8)

NAME

pvcreate ? Initialize physical volume(s) for use by LVM

SYNOPSIS

pvcreate position_args

[option_args]

DESCRIPTION

pvcreate initializes a Physical Volume (PV) on a device so the device is recognized as belonging to LVM. This allows the PV to be used in a Volume Group (VG). An LVM disk label is written to the device, and LVM metadata areas are initialized. A PV can be placed on a whole device or partition.

Use vgcreate(8) to create a new VG on the PV, or vgextend(8) to add the PV to an existing VG. Use pvremove(8) to remove the LVM disk label from the device.

The force option will create a PV without confirmation. Repeating the force option (-ff) will forcibly create a PV, overriding checks that normally prevent it, e.g. if the PV is already in a VG.

Metadata location, size, and alignment

The LVM disk label begins 512 bytes from the start of the device, and is 512 bytes in size.

The LVM metadata area begins at an offset (from the start of the device) equal to the page size of the machine creating the PV (often

4 KiB.) The metadata area contains a 512 byte header and a multi-KiB circular buffer that holds text copies of the VG metadata.

With default settings, the first physical extent (PE), which contains LV data, is 1 MiB from the start of the device. This location is controlled by `default_data_alignment` in `lvm.conf`, which is set to 1 (MiB) by default. The `pe_start` will be a multiple of this many MiB. This location can be checked with:

```
pvs -o pe_start PV
```

The size of the LVM metadata area is the space between the the start of the metadata area and the first PE. When metadata begins at 4 KiB and the first PE is at 1024 KiB, the metadata area size is 1020 KiB. This can be checked with:

```
pvs -o mda_size PV
```

The `mda_size` cannot be increased after `pvcreate`, so if larger metadata is needed, it must be set during `pvcreate`. Two copies of the VG metadata must always fit within the metadata area, so the maximum VG metadata size is around half the `mda_size`. This can be checked with:

```
vgs -o mda_free VG
```

A larger metadata area can be set with `--metadatasize`. The resulting `mda_size` may be larger than specified due to `default_data_alignment` placing `pe_start` on a MiB boundary, and the fact that the metadata area extends to the first PE. With metadata starting at 4 KiB and `default_data_alignment 1` (MiB), setting `--metadatasize 2048k` results in `pe_start` of 3 MiB and `mda_size` of 3068 KiB. Alternatively, `--metadatasize 2044k` results in `pe_start` at 2 MiB and `mda_size` of 2044 KiB.

The alignment of `pe_start` described above may be automatically overridden based on md device properties or device i/o properties reported in `sysfs`. These automatic adjustments can be enabled/disabled using `lvm.conf` settings `md_chunk_alignment` and `data_alignment_offset_detection`.

To use a different `pe_start` alignment, use the `--dataalignment` option.

The `--metadatasize` option would also typically be used in this case because the metadata area size also determines the location of `pe_start`.

When using these two options together, `pe_start` is calculated as: metadata data area start (page size), plus the specified `--metadatasize`, rounded up to the next multiple of `--dataalignment`. With metadata starting at 4 KiB, `--metadatasize 2048k`, and `--dataalignment 128k`, `pe_start` is 2176 KiB and `mda_size` is 2172 KiB. The `pe_start` of 2176 KiB is the nearest even multiple of 128 KiB that provides at least 2048 KiB of metadata space. Always check the resulting alignment and metadata size when using these options.

To shift an aligned `pe_start` value, use the `--dataalignmentoffset` option. The `pe_start` alignment is calculated as described above, and then the value specified with `--dataalignmentoffset` is added to produce the final `pe_start` value.

USAGE

`pvccreate PV ...`

[`-f|--force`]

[`-M|--metadatatype lvm2`]

[`-u|--uuid String`]

[`-Z|--zero y|n`]

[`--dataalignment Size[k|UNIT]`]

[`--dataalignmentoffset Size[k|UNIT]`]

[`--bootloaderareasize Size[m|UNIT]`]

[`--labelsector Number`]

[`--[pv]metadatacopies 0|1|2`]

[`--metadatasize Size[m|UNIT]`]

[`--metadataignore y|n`]

[`--noestorefile`]

[`--setphysicalvolumesize Size[m|UNIT]`]

[`--reportformat basic|json|json_std`]

[`--restorefile String`]

[`COMMON_OPTIONS`]

Common options for `lvm`:

[`-d|--debug`]

[`-h|--help`]

- [-q|--quiet]
- [-t|--test]
- [-v|--verbose]
- [-y|--yes]
- [--commandprofile String]
- [--config String]
- [--devices PV]
- [--devicesfile String]
- [--driverloaded y|n]
- [--journal String]
- [--lockopt String]
- [--longhelp]
- [--nohints]
- [--nolocking]
- [--profile String]
- [--version]

OPTIONS

--bootloaderareasize Size[m|UNIT]

Reserve space for the bootloader between the LVM metadata area and the first PE. The bootloader area is reserved for bootloaders to embed their own data or metadata; LVM will not use it. The bootloader area begins where the first PE would otherwise be located. The first PE is moved out by the size of the bootloader area, and then moved out further if necessary to match the data alignment. The start of the bootloader area is always aligned, see also --dataalignment and --dataalignmentoffset. The bootloader area may be larger than requested due to the alignment, but it's never less than the requested size. To see the bootloader area start and size of an existing PV use `pvs -o +pv_ba_start,pv_ba_size`.

--commandprofile String

The command profile to use for command configuration. See `lvm.conf(5)` for more information about profiles.

`--config String`

Config settings for the command. These override `lvm.conf(5)` settings. The `String` arg uses the same format as `lvm.conf(5)`, or may use section/field syntax. See `lvm.conf(5)` for more information about config.

`--dataalignment Size[k|UNIT]`

Align the start of a PV data area with a multiple of this number. To see the location of the first Physical Extent (PE) of an existing PV, use `pvs -o +pe_start`. In addition, it may be shifted by an alignment offset, see `--dataalignmentoffset`. Also specify an appropriate PE size when creating a VG.

`--dataalignmentoffset Size[k|UNIT]`

Shift the start of the PV data area by this additional offset.

`-d|--debug ...`

Set debug level. Repeat from 1 to 6 times to increase the detail of messages sent to the log file and/or syslog (if configured).

`--devices PV`

Restricts the devices that are visible and accessible to the command. Devices not listed will appear to be missing. This option can be repeated, or accepts a comma separated list of devices. This overrides the devices file.

`--devicesfile String`

A file listing devices that LVM should use. The file must exist in `/etc/lvm/devices/` and is managed with the `lvmdisks(8)` command. This overrides the `lvm.conf(5)` `devices/devicesfile` and `devices/use_devicesfile` settings.

`--driverloaded y|n`

If set to no, the command will not attempt to use device-mapper. For testing and debugging.

`-f|--force ...`

Override various checks, confirmations and protections. Use with extreme caution.

`-h|--help`

Display help text.

--journal String

Record information in the systemd journal. This information is in addition to information enabled by the lvm.conf log/journal setting. command: record information about the command. out? put: record the default command output. debug: record full command debugging.

--labelsector Number

By default the PV is labelled with an LVM2 identifier in its second sector (sector 1). This lets you use a different sector near the start of the disk (between 0 and 3 inclusive - see LABEL_SCAN_SECTORS in the source). Use with care.

--lockopt String

Used to pass options for special cases to lvmlockd. See lvmlockd(8) for more information.

--longhelp

Display long help text.

--metadataignore y|n

Specifies the metadataignore property of a PV. If yes, metadata areas on the PV are ignored, and lvm will not store metadata in the metadata areas of the PV. If no, lvm will store metadata on the PV.

--metadatasize Size[m|UNIT]

The approximate amount of space used for each VG metadata area. The size may be rounded.

-M|--metadatatype lvm2

Specifies the type of on-disk metadata to use. lvm2 (or just 2) is the current, standard format. lvm1 (or just 1) is no longer used.

--nohints

Do not use the hints file to locate devices for PVs. A command may read more devices to find PVs when hints are not used. The command will still perform standard hint file invalidation where

appropriate.

`--nolocking`

Disable locking. Use with caution, concurrent commands may produce incorrect results.

`--norestorefile`

In conjunction with `--uuid`, this allows a `uuid` to be specified without also requiring that a backup of the metadata be provided.

`--profile String`

An alias for `--commandprofile` or `--metadataprofile`, depending on the command.

`--[pv]metadatascopies 0|1|2`

The number of metadata areas to set aside on a PV for storing VG metadata. When 2, one copy of the VG metadata is stored at the front of the PV and a second copy is stored at the end. When 1, one copy of the VG metadata is stored at the front of the PV.

When 0, no copies of the VG metadata are stored on the given PV.

This may be useful in VGs containing many PVs (this places limitations on the ability to use `vgsplit` later.)

`-q|--quiet ...`

Suppress output and log messages. Overrides `--debug` and `--verbose`. Repeat once to also suppress any prompts with answer 'no'.

`--reportformat basic|json|json_std`

Overrides current output format for reports which is defined globally by the `report/output_format` setting in `lvm.conf(5)`.

`basic` is the original format with columns and rows. If there is more than one report per command, each report is prefixed with the report name for identification. `json` produces report output in JSON format. `json_std` produces report output in JSON format which is more compliant with JSON standard. See `lvmreport(7)` for more information.

`--restorefile String`

In conjunction with `--uuid`, this reads the file (produced by `vgcfgbackup`), extracts the location and size of the data on the PV, and ensures that the metadata produced by the program is consistent with the contents of the file, i.e. the physical extents will be in the same place and not be overwritten by new metadata. This provides a mechanism to upgrade the metadata format or to add/remove metadata areas. Use with care.

`--setphysicalvolumesize Size[m|UNIT]`

Overrides the automatically detected size of the PV. Use with care, or prior to reducing the physical size of the device.

`-t|--test`

Run in test mode. Commands will not update metadata. This is implemented by disabling all metadata writing but nevertheless returning success to the calling function. This may lead to unusual error messages in multi-stage operations if a tool relies on reading back metadata it believes has changed but hasn't.

`-u|--uuid String`

Specify a UUID for the device. Without this option, a random UUID is generated. This option is needed before restoring a backup of LVM metadata onto a replacement device; see `vgcfgrestore(8)`. As such, use of `--restorefile` is compulsory unless the `--norestorefile` is used. All PVs must have unique UUIDs, and LVM will prevent certain operations if multiple devices are seen with the same UUID. See `vgimportclone(8)` for more information.

`-v|--verbose ...`

Set verbose level. Repeat from 1 to 4 times to increase the default of messages sent to stdout and stderr.

`--version`

Display version information.

`-y|--yes`

Do not prompt for confirmation interactively but always assume the answer yes. Use with extreme caution. (For automatic no, see `-qq`.)

-Z|--zero y|n

Controls if the first 4 sectors (2048 bytes) of the device are wiped. The default is to wipe these sectors unless either or both of --restorefile or --uuid are specified.

VARIABLES

PV Physical Volume name, a device path under /dev. For commands managing physical extents, a PV positional arg generally accepts a suffix indicating a range (or multiple ranges) of physical extents (PEs). When the first PE is omitted, it defaults to the start of the device, and when the last PE is omitted it defaults to end. Start and end range (inclusive): PV[:PE-PE]... Start and length range (counting from 0): PV[:PE+PE]...

String See the option description for information about the string content.

Size[UNIT]

Size is an input number that accepts an optional unit. Input units are always treated as base two values, regardless of capitalization, e.g. 'k' and 'K' both refer to 1024. The default input unit is specified by letter, followed by |UNIT. UNIT represents other possible input units: b|B is bytes, s|S is sectors of 512 bytes, k|K is KiB, m|M is MiB, g|G is GiB, t|T is TiB, p|P is PiB, e|E is EiB. (This should not be confused with the output control --units, where capital letters mean multiple of 1000.)

ENVIRONMENT VARIABLES

See `lvmdiskd(8)` for information about environment variables used by `lvmdiskd`.

For example, `LVM_VG_NAME` can generally be substituted for a required VG parameter.

EXAMPLES

Initialize a partition and a full device.

```
pvcreate /dev/sdc4 /dev/sde
```

If a device is a 4 KiB sector drive that compensates for windows partitioning (sector 7 is the lowest aligned logical block, the 4 KiB sec?

tors start at LBA -1, and consequently sector 63 is aligned on a 4 KiB boundary) manually account for this when initializing for use by LVM.

```
pvcreate --dataalignmentoffset 7s /dev/sdb
```

SEE ALSO

lvm(8), lvm.conf(5), lvmconfig(8), lvmdevices(8),
pvchange(8), pvck(8), pvcreate(8), pvdisplay(8), pvmove(8),
pvremove(8), pvresize(8), pvs(8), pvscan(8),
vgcfgbackup(8), vgcfgrestore(8), vgchange(8), vgck(8), vgcreate(8),
vgconvert(8), vgdisplay(8), vgexport(8), vgextend(8), vgimport(8),
vgimportclone(8), vgimportdevices(8), vgmerge(8), vgmknodes(8),
vgreduce(8), vgremove(8), vgrename(8), vgs(8), vgscan(8), vgsplit(8),
lvcreate(8), lvchange(8), lvconvert(8), lvdisplay(8), lvextend(8),
lvreduce(8), lvremove(8), lvrename(8), lvresize(8), lvs(8), lvscan(8),
lvm-fullreport(8), lvm-lvpoll(8), blkdeactivate(8), lvmdump(8),
dmeventd(8), lvmpolld(8), lvmlockd(8), lvmlockctl(8), cmirrord(8),
lvmdbusd(8), fsadm(8),
lvmsystemid(7), lvmreport(7), lvraid(7), lvthin(7), lvncache(7)

Red Hat, Inc. LVM TOOLS 2.03.17(2) (2022-11-10) PVCREATE(8)