



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'realpath.1' command

\$ man realpath.1

REALPATH(1) User Commands REALPATH(1)

NAME

realpath - print the resolved path

SYNOPSIS

realpath [OPTION]... FILE...

DESCRIPTION

Print the resolved absolute file name; all but the last component must exist

-e, --canonicalize-existing

all components of the path must exist

-m, --canonicalize-missing

no path components need exist or be a directory

-L, --logical

resolve '..' components before symlinks

-P, --physical

resolve symlinks as encountered (default)

-q, --quiet

suppress most error messages

--relative-to=DIR

print the resolved path relative to DIR

--relative-base=DIR

print absolute paths unless paths below DIR

-s, --strip, --no-symlinks

don't expand symlinks

-z, --zero

end each output line with NUL, not newline

--help display this help and exit

--version

output version information and exit

AUTHOR

Written by Padraig Brady.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2020 Free Software Foundation, Inc. License GPLv3+: GNU

GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

`readlink(1)`, `readlink(2)`, `realpath(3)`

Full documentation <<https://www.gnu.org/software/coreutils/realpath>>

or available locally via: `info '(coreutils) realpath invocation'`

GNU coreutils 8.32

January 2023

REALPATH(1)