Red Hat Enterprise Linux Release 9.2 Manual Pages on 'rhsm-debug.8' command

$ man rhsm-debug.8

RHSM-DEBUG(8)   RHSM Debug Tool   RHSM-DEBUG(8)

NAME

   rhsm-debug - Compiles information about system's entitlements, prod?

   ucts, and identity used by Red Hat Subscription Manager.

SYNOPSIS

   rhsm-debug module [options]

DESCRIPTION

   rhsm-debug compiles information about system's entitlements, products,

   and identity used by Red Hat Subscription Manager.

COMMANDS AND OPTIONS

   rhsm-debug has specific options available for each module, depending on

   what operation is being performed. The currently supported modules are:

       1. system

  COMMON OPTIONS

   -h, --help

       Prints the specific help information for the given command.

   --proxy=PROXY

       Uses an HTTP proxy. The PROXY name has the format hostname:port.

   --proxyuser=PROXYUSERNAME

       Gives the username to use to authenticate to the HTTP proxy.

   --proxypassword=PROXYPASSWORD

       Gives the password to use to authenticate to the HTTP proxy.

SYSTEM OPTIONS

The system command pulls in debug information off of the current system

--destination=DESTINATION

   The directory to place the resulting debug data. The default is

   /tmp.

--no-archive

   Generates an uncompressed directory instead of a gzipped file.

--sos Excludes data files that are also collected by the sosreport

   tool.

BUGS

   This tool is part of Red Hat Subscription Manager. To file bugs against

   this command-line tool, go to <https://bugzilla.redhat.com>, and select

   Red Hat > Red Hat Enterprise Linux > subscription-manager.

AUTHORS

   William Poteat<wpoteat@redhat.com>. The rhsm-debug tool was written by

   William Poteat.

COPYRIGHT

   Copyright (c) 2012 Red Hat, Inc. This is licensed under the GNU General

   Public License, version 2 (GPLv2). A copy of this license is available

   at http://www.gnu.org/licenses/old-licenses/gpl-2.0.txt.

<p align="center">RHSM-DEBUG(8)</p>