



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'rwwarray.3am' command

\$ man rwwarray.3am

RWARRAY(3am) GNU Awk Extension Modules RWARRAY(3am)

NAME

writea, reada - write and read gawk arrays to/from files

SYNOPSIS

```
@load "rwwarray"
```

```
ret = writea(file, array)
```

```
ret = reada(file, array)
```

DESCRIPTION

The rwwarray extension adds two functions named writea(). and reada(), as follows.

writea()

This function takes a string argument, which is the name of the file to which dump the array, and the array itself as the second argument. writea() understands multidimensional arrays. It returns one on success, or zero upon failure.

reada()

is the inverse of writea(); it reads the file named as its first argument, filling in the array named as the second argument. It clears the array first. Here too, the return value is one on success and zero upon failure.

NOTES

The array created by reada() is identical to that written by writea() in the sense that the contents are the same. However, due to implemen?

tation issues, the array traversal order of the recreated array will likely be different from that of the original array. As array traversal order in AWK is by default undefined, this is not (technically) a problem. If you need to guarantee a particular traversal order, use the array sorting features in gawk to do so.

The file contains binary data. All integral values are written in network byte order. However, double precision floating-point values are written as native binary data. Thus, arrays containing only string data can theoretically be dumped on systems with one byte order and re-stored on systems with a different one, but this has not been tried.

EXAMPLE

```
@load "rvarray"  
  
...  
ret = writea("arraydump.bin", array)  
  
...  
ret = reada("arraydump.bin", array)
```

SEE ALSO

GAWK: Effective AWK Programming, filefuncs(3am), fnmatch(3am), fork(3am), inplace(3am), ordchr(3am), readdir(3am), readfile(3am), revoutput(3am), time(3am).

AUTHOR

Arnold Robbins, arnold@skeeve.com.

COPYING PERMISSIONS

Copyright ? 2012, 2013, 2018, Free Software Foundation, Inc.

Permission is granted to make and distribute verbatim copies of this manual page provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual page under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual page into another language, under the above conditions for modified

versions, except that this permission notice may be stated in a trans?

lation approved by the Foundation.

Free Software Foundation

Feb 02 2018

RWARRAY(3am)