



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'semanage-interface.8' command

\$ man semanage-interface.8

semanage-interface(8) semanage-interface(8)

NAME

semanage-interface - SELinux Policy Management network interface tool

SYNOPSIS

```
semanage interface [-h] [-n] [-N] [-S STORE] [ --add -t TYPE -r RANGE
interface | --delete interface | --deleteall | --extract | --list [-C]
| --modify -t TYPE -r RANGE interface ]
```

DESCRIPTION

semanage is used to configure certain elements of SELinux policy with?
out requiring modification to or recompilation from policy sources.
semanage interface controls the labels assigned to network interfaces.

OPTIONS

-h, --help
show this help message and exit

-n, --noheading
Do not print heading when listing the specified object type

-N, --noreload
Do not reload policy after commit

-S STORE, --store STORE
Select an alternate SELinux Policy Store to manage

-C, --locallist
List local customizations

-a, --add

Add a record of the specified object type

-d, --delete

Delete a record of the specified object type

-m, --modify

Modify a record of the specified object type

-l, --list

List records of the specified object type

-E, --extract

Extract customizable commands, for use within a transaction

-D, --deleteall

Remove all local customizations

-t TYPE, --type TYPE

SELinux type for the object

-r RANGE, --range RANGE

MLS/MCS Security Range (MLS/MCS Systems only) SELinux Range for

SELinux login mapping defaults to the SELinux user record range.

SELinux Range for SELinux user defaults to s0.

EXAMPLE

list all interface definitions

```
# semanage interface -l
```

SEE ALSO

selinux(8), semanage(8)

AUTHOR

This man page was written by Daniel Walsh <dwalsh@redhat.com>

20130617

semanage-interface(8)