



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'sgp\_dd.8' command**

**\$ man sgp\_dd.8**

SGP\_DD(8) SG3\_UTILS SGP\_DD(8)

### **NAME**

sgp\_dd - copy data to and from files and devices, especially SCSI de?

vices

### **SYNOPSIS**

```
sgp_dd [bs=BS] [count=COUNT] [ibs=BS] [if=FILE] [iflag=FLAGS] [obs=BS]
[of=OFILE] [oflag=FLAGS] [seek=SEEK] [skip=SKIP] [--help] [--version]
[bpt=BPT] [coe=0|1] [cdbsz=6|10|12|16] [deb=VERB] [dio=0|1] [sync=0|1]
[thr=THR] [time=0|1] [verbose=VERB] [--chkaddr] [--dry-run] [--verbose]
```

### **DESCRIPTION**

Copy data to and from any files. Specialised for "files" that are Linux SCSI generic (sg) and raw devices. Similar syntax and semantics to dd(1) but does not perform any conversions. Uses POSIX threads (often called "pthreads") to increase the amount of parallelism. This improves speed in some cases.

The first group in the synopsis above are "standard" Unix dd(1) options. The second group are extra options added by this utility. Both groups are defined below.

### **OPTIONS**

**bpt=BPT**

each IO transaction will be made using BPT blocks (or less if near the end of the copy). Default is 128 for block sizes less than 2048 bytes, otherwise the default is 32. So for bs=512 the

reads and writes will each convey 64 KiB of data by default (less if near the end of the transfer or memory restrictions).

When cd/dvd drives are accessed, the block size is typically 2048 bytes and bpt defaults to 32 which again implies 64 KiB transfers.

bs=BS where BS must be the block size of the physical device. Note that this differs from dd(1) which permits 'bs' to be an integral multiple of the actual device block size. Default is 512 which is usually correct for disks but incorrect for cdroms (which normally have 2048 byte blocks).

cdbsz=6 | 10 | 12 | 16

size of SCSI READ and/or WRITE commands issued on sg device names. Default is 10 byte SCSI command blocks (unless calculations indicate that a 4 byte block number may be exceeded, in which case it defaults to 16 byte SCSI commands).

coe=0 | 1

set to 1 for continue on error. Only applies to errors on sg devices. Thus errors on other files will stop sgp\_dd. Default is 0 which implies stop on any error. See the 'coe' flag for more information.

count=COUNT

copy COUNT blocks from IFILE to OFILE. Default is the minimum (of IFILE and OFILE) number of blocks that sg devices report from SCSI READ CAPACITY commands or that block devices (or their partitions) report. Normal files are not probed for their size.

If skip=SKIP or seek=SEEK are given and the count is deduced (i.e. not explicitly given) then that count is scaled back so that the copy will not overrun the device. If the file name is a block device partition and COUNT is not given then the size of the partition rather than the size of the whole device is used.

If COUNT is not given and cannot be deduced then an error message is issued and no copy takes place.

deb=VERB

outputs debug information. If VERB is 0 (default) then there is minimal debug information and as VERB increases so does the amount of debug (max debug output when VERB is 9).

**dio=0 | 1**

default is 0 which selects indirect IO. Value of 1 attempts direct IO which, if not available, falls back to indirect IO and notes this at completion. If direct IO is selected and /proc/scsi/sg/allow\_dio has the value of 0 then a warning is issued (and indirect IO is performed) For finer grain control use 'iflag=dio' or 'oflag=dio'.

**ibs=BS** if given must be the same as BS given to 'bs=' option.

**if=IFILE**

read from IFILE instead of stdin. If IFILE is '-' then stdin is read. Starts reading at the beginning of IFILE unless SKIP is given.

**iflag=FLAGS**

where FLAGS is a comma separated list of one or more flags outlined below. These flags are associated with IFILE and are ignored when IFILE is stdin.

**obs=BS** if given must be the same as BS given to 'bs=' option.

**of=OFILE**

write to OFILE instead of stdout. If OFILE is '-' then writes to stdout. If OFILE is /dev/null then no actual writes are performed. If OFILE is '.' (period) then it is treated the same way as /dev/null (this is a shorthand notation). If OFILE exists then it is \_not\_ truncated; it is overwritten from the start of OFILE unless 'oflag=append' or SEEK is given.

**oflag=FLAGS**

where FLAGS is a comma separated list of one or more flags outlined below. These flags are associated with OFILE and are ignored when OFILE is /dev/null, '.' (period), or stdout.

**seek=SEEK**

start writing SEEK bs-sized blocks from the start of OFILE. De?

fault is block 0 (i.e. start of file).

skip=SKIP

start reading SKIP bs-sized blocks from the start of IFILE. De?

fault is block 0 (i.e. start of file).

sync=0 | 1

when 1, does SYNCHRONIZE CACHE command on OFILE at the end of the transfer. Only active when OFILE is a sg device file name.

thr=THR

where THR is the number of worker threads (default 4) that attempt to copy in parallel. Minimum is 1 and maximum is 1024.

time=0 | 1

when 1, the transfer is timed and throughput calculation is performed, outputting the results (to stderr) at completion. When 0 (default) no timing is performed.

verbose=VERB

increase verbosity. Same as deb=VERB. Added for compatibility with sg\_dd and sgm\_dd.

-c, --chkaddr

this option checks that every block read contains the (32 bit) block address of that block. If that check fails, the copy exits with a miscompare error. This check complements the 'sg\_dd iflag=00,ff' generation of blocks that contain their own (32 bit, big endian) block address. When --chkaddr is used once, only the first block address in each block is checked. When used twice, each block address (that fits in a block) is checked.

-d, --dry-run

does all the command line parsing and preparation but bypasses the actual copy or read. That preparation may include opening IFILE or OFILE to determine their lengths. This option may be useful for testing the syntax of complex command line invocations in advance of executing them.

-h, --help

outputs usage message and exits.

-v, --verbose

when used once, this is equivalent to verbose=1. When used twice (e.g. "-vv") this is equivalent to verbose=2, etc.

-V, --version

outputs version number information and exits.

## FLAGS

Here is a list of flags and their meanings:

append causes the O\_APPEND flag to be added to the open of OFILE. For normal files this will lead to data appended to the end of any existing data. Cannot be used together with the seek=SEEK op? tion as they conflict. The default action of this utility is to overwrite any existing data from the beginning of the file or, if SEEK is given, starting at block SEEK. Note that attempting to 'append' to a device file (e.g. a disk) will usually be ignored or may cause an error to be reported.

coe continue on error. When given with 'iflag=', an error that is detected in a single SCSI command (typically 'bpt' blocks) is noted (by an error message sent to stderr), then zeros are substituted into the buffer for the corresponding write operation and the copy continues. Note that the sg\_dd utility is more sophisticated in such error situations when 'iflag=coe'. When given with 'oflag=', any error reported by a SCSI WRITE command is reported to stderr and the copy continues (as if nothing went wrong).

dio request the sg device node associated with this flag does direct IO. If direct IO is not available, falls back to indirect IO and notes this at completion. If direct IO is selected and /proc/scsi/sg/allow\_dio has the value of 0 then a warning is issued (and indirect IO is performed).

direct causes the O\_DIRECT flag to be added to the open of IFILE and/or OFILE. This flag requires some memory alignment on IO. Hence user memory buffers are aligned to the page size. Has no effect on sg, normal or raw files.

dpo set the DPO bit (disable page out) in SCSI READ and WRITE com?

mands. Not supported for 6 byte cdb variants of READ and WRITE.

Indicates that data is unlikely to be required to stay in device

(e.g. disk) cache. May speed media copy and/or cause a media copy to have less impact on other device users.

dsync causes the O\_SYNC flag to be added to the open of IFILE and/or OFILE. The 'd' is prepended to lower confusion with the 'sync=0|1' option which has another action (i.e. a synchronisation to media at the end of the transfer).

excl causes the O\_EXCL flag to be added to the open of IFILE and/or OFILE.

mmap can only be used in the iflag=FLAGS or the oflag=FLAGS argument list but not both. The nominated side of the copy will use memory mapped IO based on the mmap(2) system call. The sg driver will remap its DMA destination or source buffer into the user space when the mmap(2) system call is used on a sg device.

fua causes the FUA (force unit access) bit to be set in SCSI READ and/or WRITE commands. This only has effect with sg devices. The 6 byte variants of the SCSI READ and WRITE commands do not support the FUA bit. Only active for sg device file names.

null has no affect, just a placeholder.

## RETIRED OPTIONS

Here are some retired options that are still present:

coe=0 | 1

continue on error is 0 (off) by default. When it is 1, it is equivalent to 'iflag=coe oflag=coe' described in the FLAGS section above. Similar to 'conv=noerror,sync' in dd(1) utility.

Default is 0 which implies stop on error. More advanced coe=1 processing on reads is performed by the sg\_dd utility.

fua=0 | 1 | 2 | 3

force unit access bit. When 3, fua is set on both IFILE and OFILE; when 2, fua is set on IFILE; when 1, fua is set on OFILE; when 0 (default), fua is cleared on both. See the 'fua'

flag.

## NOTES

A raw device must be bound to a block device prior to using sgp\_dd.

See raw(8) for more information about binding raw devices. To be safe, the sg device mapping to SCSI block devices should be checked with 'cat /proc/scsi/scsi' before use.

Raw device partition information can often be found with fdisk(8) [the "-ul" argument is useful in this respect].

Various numeric arguments (e.g. SKIP) may include multiplicative suf? fixes or be given in hexadecimal. See the "NUMERIC ARGUMENTS" section in the sg3\_utils(8) man page.

The COUNT, SKIP and SEEK arguments can take 64 bit values (i.e. very big numbers). Other values are limited to what can fit in a signed 32 bit number.

Data usually gets to the user space in a 2 stage process: first the SCSI adapter DMAs into kernel buffers and then the sg driver copies this data into user memory (write operations reverse this sequence).

This is called "indirect IO" and there is a 'dio' option to select "direct IO" which will DMA directly into user memory. Due to some issues "direct IO" is disabled in the sg driver and needs a configuration change to activate it.

All informative, warning and error output is sent to stderr so that dd's output file can be stdout and remain unpolluted. If no options are given, then the usage message is output and nothing else happens.

Why use sgp\_dd? Because in some cases it is twice as fast as dd (mainly with sg devices, raw devices give some improvement). Another reason is that big copies fill the block device caches which has a negative impact on other machine activity.

## SIGNALS

The signal handling has been borrowed from dd: SIGINT, SIGQUIT and SIGPIPE output the number of remaining blocks to be transferred and the records in + out counts; then they have their default action. SIGUSR1 causes the same information to be output yet the copy continues. All

output caused by signals is sent to stderr.

## EXAMPLES

Looks quite similar in usage to dd:

```
sgp_dd if=/dev/sg0 of=t bs=512 count=1MB
```

This will copy 1 million 512 byte blocks from the device associated

with /dev/sg0 (which should have 512 byte blocks) to a file called t.

Assuming /dev/sda and /dev/sg0 are the same device then the above is equivalent to:

```
dd if=/dev/sda of=t bs=512 count=1000000
```

although dd's speed may improve if bs was larger and count was corre?

spondingly scaled. Using a raw device to do something similar on a ATA disk:

```
raw /dev/raw/raw1 /dev/hda
```

```
sgp_dd if=/dev/raw/raw1 of=t bs=512 count=1MB
```

To copy a SCSI disk partition to an ATA disk partition:

```
raw /dev/raw/raw2 /dev/hda3
```

```
sgp_dd if=/dev/sg0 skip=10123456 of=/dev/raw/raw2 bs=512
```

This assumes a valid partition is found on the SCSI disk at the given

skip block address (past the 5 GB point of that disk) and that the par?

tion goes to the end of the SCSI disk. An explicit count is probably

a safer option.

To do a fast copy from one SCSI disk to another one with similar geome?

try (stepping over errors on the source disk):

```
sgp_dd if=/dev/sg0 of=/dev/sg1 bs=512 coe=1
```

## EXIT STATUS

The exit status of sgp\_dd is 0 when it is successful. Otherwise see the

sg3\_utils(8) man page. Since this utility works at a higher level than

individual commands, and there are 'coe' and 'retries' flags, individ?

ual SCSI command failures do not necessary cause the process to exit.

## AUTHORS

Written by Douglas Gilbert and Peter Allworth.

## REPORTING BUGS

Report bugs to <dgilbert at interlog dot com>.

## COPYRIGHT

Copyright ? 2000-2021 Douglas Gilbert

This software is distributed under the GPL version 2. There is NO war?  
ranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PUR?  
POSE.

## SEE ALSO

A simpler, non-threaded version of this utility but with more advanced  
"continue on error" logic is called sg\_dd and is also found in the  
sg3\_utils package. The lmbench package contains lmdd which is also in?  
teresting. raw(8), dd(1)

sg3\_utils-1.47

October 2021

SGP\_DD(8)