



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'sk_TYPE_find_all.3openssl' command

\$ man sk_TYPE_find_all.3openssl

DEFINE_STACK_OF(3openssl) OpenSSL DEFINE_STACK_OF(3openssl)

NAME

DEFINE_STACK_OF, DEFINE_STACK_OF_CONST, DEFINE_SPECIAL_STACK_OF,
DEFINE_SPECIAL_STACK_OF_CONST, sk_TYPE_num, sk_TYPE_value, sk_TYPE_new,
sk_TYPE_new_null, sk_TYPE_reserve, sk_TYPE_free, sk_TYPE_zero,
sk_TYPE_delete, sk_TYPE_delete_ptr, sk_TYPE_push, sk_TYPE_unshift,
sk_TYPE_pop, sk_TYPE_shift, sk_TYPE_pop_free, sk_TYPE_insert,
sk_TYPE_set, sk_TYPE_find, sk_TYPE_find_ex, sk_TYPE_find_all,
sk_TYPE_sort, sk_TYPE_is_sorted, sk_TYPE_dup, sk_TYPE_deep_copy,
sk_TYPE_set_cmp_func, sk_TYPE_new_reserve, OPENSSL_sk_deep_copy,
OPENSSL_sk_delete, OPENSSL_sk_delete_ptr, OPENSSL_sk_dup,
OPENSSL_sk_find, OPENSSL_sk_find_ex, OPENSSL_sk_find_all,
OPENSSL_sk_free, OPENSSL_sk_insert, OPENSSL_sk_is_sorted,
OPENSSL_sk_new, OPENSSL_sk_new_null, OPENSSL_sk_new_reserve,
OPENSSL_sk_num, OPENSSL_sk_pop, OPENSSL_sk_pop_free, OPENSSL_sk_push,
OPENSSL_sk_reserve, OPENSSL_sk_set, OPENSSL_sk_set_cmp_func,
OPENSSL_sk_shift, OPENSSL_sk_sort, OPENSSL_sk_unshift,
OPENSSL_sk_value, OPENSSL_sk_zero - stack container

SYNOPSIS

```
#include <openssl/safestack.h>

STACK_OF(TYPE)

DEFINE_STACK_OF(TYPE)

DEFINE_STACK_OF_CONST(TYPE)
```

```

DEFINE_SPECIAL_STACK_OF(FUNCTYPE, TYPE)
DEFINE_SPECIAL_STACK_OF_CONST(FUNCTYPE, TYPE)
typedef int (*sk_TYPE_compfunc)(const TYPE *const *a, const TYPE *const *b);
typedef TYPE * (*sk_TYPE_copyfunc)(const TYPE *a);
typedef void (*sk_TYPE_freefunc)(TYPE *a);
int sk_TYPE_num(const STACK_OF(TYPE) *sk);
TYPE *sk_TYPE_value(const STACK_OF(TYPE) *sk, int idx);
STACK_OF(TYPE) *sk_TYPE_new(sk_TYPE_compfunc compare);
STACK_OF(TYPE) *sk_TYPE_new_null(void);
int sk_TYPE_reserve(STACK_OF(TYPE) *sk, int n);
void sk_TYPE_free(const STACK_OF(TYPE) *sk);
void sk_TYPE_zero(const STACK_OF(TYPE) *sk);
TYPE *sk_TYPE_delete(STACK_OF(TYPE) *sk, int i);
TYPE *sk_TYPE_delete_ptr(STACK_OF(TYPE) *sk, TYPE *ptr);
int sk_TYPE_push(STACK_OF(TYPE) *sk, const TYPE *ptr);
int sk_TYPE_unshift(STACK_OF(TYPE) *sk, const TYPE *ptr);
TYPE *sk_TYPE_pop(STACK_OF(TYPE) *sk);
TYPE *sk_TYPE_shift(STACK_OF(TYPE) *sk);
void sk_TYPE_pop_free(STACK_OF(TYPE) *sk, sk_TYPE_freefunc freefunc);
int sk_TYPE_insert(STACK_OF(TYPE) *sk, TYPE *ptr, int idx);
TYPE *sk_TYPE_set(STACK_OF(TYPE) *sk, int idx, const TYPE *ptr);
int sk_TYPE_find(STACK_OF(TYPE) *sk, TYPE *ptr);
int sk_TYPE_find_ex(STACK_OF(TYPE) *sk, TYPE *ptr);
int sk_TYPE_find_all(STACK_OF(TYPE) *sk, TYPE *ptr, int *pnum);
void sk_TYPE_sort(const STACK_OF(TYPE) *sk);
int sk_TYPE_is_sorted(const STACK_OF(TYPE) *sk);
STACK_OF(TYPE) *sk_TYPE_dup(const STACK_OF(TYPE) *sk);
STACK_OF(TYPE) *sk_TYPE_deep_copy(const STACK_OF(TYPE) *sk,
                                sk_TYPE_copyfunc copyfunc,
                                sk_TYPE_freefunc freefunc);
sk_TYPE_compfunc (*sk_TYPE_set_cmp_func(STACK_OF(TYPE) *sk,
                                        sk_TYPE_compfunc compare));
STACK_OF(TYPE) *sk_TYPE_new_reserve(sk_TYPE_compfunc compare, int n);

```

DESCRIPTION

Applications can create and use their own stacks by placing any of the macros described below in a header file. These macros define typesafe inline functions that wrap around the utility `OPENSSL_sk_` API. In the description here, `TYPE` is used as a placeholder for any of the OpenSSL datatypes, such as `X509`.

The `STACK_OF()` macro returns the name for a stack of the specified `TYPE`. This is an opaque pointer to a structure declaration. This can be used in every header file that references the stack. There are several `DEFINE...` macros that create static inline functions for all of the functions described on this page. This should normally be used in one source file, and the stack manipulation is wrapped with application-specific functions.

`DEFINE_STACK_OF()` creates set of functions for a stack of `TYPE` elements. The type is referenced by `STACK_OF(TYPE)` and each function name begins with `sk_TYPE_`. `DEFINE_STACK_OF_CONST()` is identical to `DEFINE_STACK_OF()` except each element is constant.

```
/* DEFINE_STACK_OF(TYPE) */
```

```
TYPE *sk_TYPE_value(STACK_OF(TYPE) *sk, int idx);
```

```
/* DEFINE_STACK_OF_CONST(TYPE) */
```

```
const TYPE *sk_TYPE_value(STACK_OF(TYPE) *sk, int idx);
```

`DEFINE_SPECIAL_STACK_OF()` and `DEFINE_SPECIAL_STACK_OF_CONST()` are similar except `FUNCNAME` is used in the function names:

```
/* DEFINE_SPECIAL_STACK_OF(TYPE, FUNCNAME) */
```

```
TYPE *sk_FUNCNAME_value(STACK_OF(TYPE) *sk, int idx);
```

```
/* DEFINE_SPECIAL_STACK_OF(TYPE, FUNCNAME) */
```

```
const TYPE *sk_FUNCNAME_value(STACK_OF(TYPE) *sk, int idx);
```

`sk_TYPE_num()` returns the number of elements in `sk` or `-1` if `sk` is `NULL`.

`sk_TYPE_value()` returns element `idx` in `sk`, where `idx` starts at zero. If `idx` is out of range then `NULL` is returned.

`sk_TYPE_new()` allocates a new empty stack using comparison function `compare`. If `compare` is `NULL` then no comparison function is used. This function is equivalent to `sk_TYPE_new_reserve(compare, 0)`.

`sk_TYPE_new_null()` allocates a new empty stack with no comparison function. This function is equivalent to `sk_TYPE_new_reserve(NULL, 0)`. `sk_TYPE_reserve()` allocates additional memory in the `sk` structure such that the next `n` calls to `sk_TYPE_insert()`, `sk_TYPE_push()` or `sk_TYPE_unshift()` will not fail or cause memory to be allocated or reallocated. If `n` is zero, any excess space allocated in the `sk` structure is freed. On error `sk` is unchanged.

`sk_TYPE_new_reserve()` allocates a new stack. The new stack will have additional memory allocated to hold `n` elements if `n` is positive. The next `n` calls to `sk_TYPE_insert()`, `sk_TYPE_push()` or `sk_TYPE_unshift()` will not fail or cause memory to be allocated or reallocated. If `n` is zero or less than zero, no memory is allocated. `sk_TYPE_new_reserve()` also sets the comparison function `compare` to the newly created stack. If `compare` is `NULL` then no comparison function is used.

`sk_TYPE_set_cmp_func()` sets the comparison function of `sk` to `compare`. The previous comparison function is returned or `NULL` if there was no previous comparison function.

`sk_TYPE_free()` frees up the `sk` structure. It does not free up any elements of `sk`. After this call `sk` is no longer valid.

`sk_TYPE_zero()` sets the number of elements in `sk` to zero. It does not free `sk` so after this call `sk` is still valid.

`sk_TYPE_pop_free()` frees up all elements of `sk` and `sk` itself. The free function `freefunc()` is called on each element to free it.

`sk_TYPE_delete()` deletes element `i` from `sk`. It returns the deleted element or `NULL` if `i` is out of range.

`sk_TYPE_delete_ptr()` deletes element matching `ptr` from `sk`. It returns the deleted element or `NULL` if no element matching `ptr` was found.

`sk_TYPE_insert()` inserts `ptr` into `sk` at position `idx`. Any existing elements at or after `idx` are moved downwards. If `idx` is out of range the new element is appended to `sk`. `sk_TYPE_insert()` either returns the number of elements in `sk` after the new element is inserted or zero if an error (such as memory allocation failure) occurred.

`sk_TYPE_push()` appends `ptr` to `sk` it is equivalent to:

`sk_TYPE_insert(sk, ptr, -1);`

`sk_TYPE_unshift()` inserts `ptr` at the start of `sk` it is equivalent to:

`sk_TYPE_insert(sk, ptr, 0);`

`sk_TYPE_pop()` returns and removes the last element from `sk`.

`sk_TYPE_shift()` returns and removes the first element from `sk`.

`sk_TYPE_set()` sets element `idx` of `sk` to `ptr` replacing the current element. The new element value is returned or `NULL` if an error occurred: this will only happen if `sk` is `NULL` or `idx` is out of range.

`sk_TYPE_find()` searches `sk` for the element `ptr`. In the case where no comparison function has been specified, the function performs a linear search for a pointer equal to `ptr`. The index of the first matching element is returned or `-1` if there is no match. In the case where a comparison function has been specified, `sk` is sorted and `sk_TYPE_find()` returns the index of a matching element or `-1` if there is no match.

Note that, in this case the comparison function will usually compare the values pointed to rather than the pointers themselves and the order of elements in `sk` can change. Note that because the stack may be sorted as the result of a `sk_TYPE_find()` call, if a lock is being used to synchronise access to the stack across multiple threads, then that lock must be a "write" lock.

`sk_TYPE_find_ex()` operates like `sk_TYPE_find()` except when a comparison function has been specified and no matching element is found. Instead of returning `-1`, `sk_TYPE_find_ex()` returns the index of the element either before or after the location where `ptr` would be if it were present in `sk`. The function also does not guarantee that the first matching element in the sorted stack is returned.

`sk_TYPE_find_all()` operates like `sk_TYPE_find()` but it also sets the `*pnum` to number of matching elements in the stack. In case no comparison function has been specified the `*pnum` will be always set to 1 if matching element was found, 0 otherwise.

`sk_TYPE_sort()` sorts `sk` using the supplied comparison function.

`sk_TYPE_is_sorted()` returns 1 if `sk` is sorted and 0 otherwise.

`sk_TYPE_dup()` returns a shallow copy of `sk` or an empty stack if the

passed stack is NULL. Note the pointers in the copy are identical to the original.

sk_TYPE_deep_copy() returns a new stack where each element has been copied or an empty stack if the passed stack is NULL. Copying is performed by the supplied copyfunc() and freeing by freefunc(). The function freefunc() is only called if an error occurs.

NOTES

Care should be taken when accessing stacks in multi-threaded environments. Any operation which increases the size of a stack such as sk_TYPE_insert() or sk_TYPE_push() can "grow" the size of an internal array and cause race conditions if the same stack is accessed in a different thread. Operations such as sk_TYPE_find() and sk_TYPE_sort() can also reorder the stack.

Any comparison function supplied should use a metric suitable for use in a binary search operation. That is it should return zero, a positive or negative value if a is equal to, greater than or less than b respectively.

Care should be taken when checking the return values of the functions sk_TYPE_find() and sk_TYPE_find_ex(). They return an index to the matching element. In particular 0 indicates a matching first element.

A failed search is indicated by a -1 return value.

STACK_OF(), DEFINE_STACK_OF(), DEFINE_STACK_OF_CONST(), and DEFINE_SPECIAL_STACK_OF() are implemented as macros.

It is not an error to call sk_TYPE_num(), sk_TYPE_value(), sk_TYPE_free(), sk_TYPE_zero(), sk_TYPE_pop_free(), sk_TYPE_delete(), sk_TYPE_delete_ptr(), sk_TYPE_pop(), sk_TYPE_shift(), sk_TYPE_find(), sk_TYPE_find_ex(), and sk_TYPE_find_all() on a NULL stack, empty stack, or with an invalid index. An error is not raised in these conditions.

The underlying utility OPENSSL_sk_ API should not be used directly. It defines these functions: OPENSSL_sk_deep_copy(), OPENSSL_sk_delete(), OPENSSL_sk_delete_ptr(), OPENSSL_sk_dup(), OPENSSL_sk_find(), OPENSSL_sk_find_ex(), OPENSSL_sk_find_all(), OPENSSL_sk_free(), OPENSSL_sk_insert(), OPENSSL_sk_is_sorted(), OPENSSL_sk_new(),

OPENSSL_sk_new_null(), OPENSSL_sk_new_reserve(), OPENSSL_sk_num(),
OPENSSL_sk_pop(), OPENSSL_sk_pop_free(), OPENSSL_sk_push(),
OPENSSL_sk_reserve(), OPENSSL_sk_set(), OPENSSL_sk_set_cmp_func(),
OPENSSL_sk_shift(), OPENSSL_sk_sort(), OPENSSL_sk_unshift(),
OPENSSL_sk_value(), OPENSSL_sk_zero().

RETURN VALUES

sk_TYPE_num() returns the number of elements in the stack or -1 if the passed stack is NULL.

sk_TYPE_value() returns a pointer to a stack element or NULL if the index is out of range.

sk_TYPE_new(), sk_TYPE_new_null() and sk_TYPE_new_reserve() return an empty stack or NULL if an error occurs.

sk_TYPE_reserve() returns 1 on successful allocation of the required memory or 0 on error.

sk_TYPE_set_cmp_func() returns the old comparison function or NULL if there was no old comparison function.

sk_TYPE_free(), sk_TYPE_zero(), sk_TYPE_pop_free() and sk_TYPE_sort() do not return values.

sk_TYPE_pop(), sk_TYPE_shift(), sk_TYPE_delete() and sk_TYPE_delete_ptr() return a pointer to the deleted element or NULL on error.

sk_TYPE_insert(), sk_TYPE_push() and sk_TYPE_unshift() return the total number of elements in the stack and 0 if an error occurred.

sk_TYPE_push() further returns -1 if sk is NULL.

sk_TYPE_set() returns a pointer to the replacement element or NULL on error.

sk_TYPE_find() and sk_TYPE_find_ex() return an index to the found element or -1 on error.

sk_TYPE_is_sorted() returns 1 if the stack is sorted and 0 if it is not.

sk_TYPE_dup() and sk_TYPE_deep_copy() return a pointer to the copy of the stack or NULL on error.

HISTORY

Before OpenSSL 1.1.0, this was implemented via macros and not inline functions and was not a public API.

sk_TYPE_reserve() and sk_TYPE_new_reserve() were added in OpenSSL 1.1.1.

COPYRIGHT

Copyright 2000-2022 The OpenSSL Project Authors. All Rights Reserved.
Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 DEFINE_STACK_OF(3ossl)