



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'systemd-shutdown.8' command**

**\$ man systemd-shutdown.8**

SYSTEMD-HALT.SERVICE(8)    systemd-halt.service    SYSTEMD-HALT.SERVICE(8)

### **NAME**

systemd-halt.service, systemd-poweroff.service, systemd-reboot.service,  
systemd-kexec.service, systemd-shutdown - System shutdown logic

### **SYNOPSIS**

systemd-halt.service  
systemd-poweroff.service  
systemd-reboot.service  
systemd-kexec.service  
/usr/lib/systemd/systemd-shutdown  
/usr/lib/systemd/system-shutdown/

### **DESCRIPTION**

systemd-halt.service is a system service that is pulled in by  
halt.target and is responsible for the actual system halt. Similarly,  
systemd-poweroff.service is pulled in by poweroff.target,  
systemd-reboot.service by reboot.target and systemd-kexec.service by  
kexec.target to execute the respective actions.

When these services are run, they ensure that PID 1 is replaced by the  
/usr/lib/systemd/systemd-shutdown tool which is then responsible for  
the actual shutdown. Before shutting down, this binary will try to  
unmount all remaining file systems, disable all remaining swap devices,  
detach all remaining storage devices and kill all remaining processes.

It is necessary to have this code in a separate binary because

otherwise rebooting after an upgrade might be broken ? the running PID 1 could still depend on libraries which are not available any more, thus keeping the file system busy, which then cannot be re-mounted read-only.

Immediately before executing the actual system

halt/poweroff/reboot/kexec systemd-shutdown will run all executables in /usr/lib/systemd/system-shutdown/ and pass one arguments to them: either "halt", "poweroff", "reboot" or "kexec", depending on the chosen action. All executables in this directory are executed in parallel, and execution of the action is not continued before all executables finished.

Note that systemd-halt.service (and the related units) should never be executed directly. Instead, trigger system shutdown with a command such as "systemctl halt" or suchlike.

## SEE ALSO

systemd(1), systemctl(1), systemd.special(7), reboot(2), systemd-suspend.service(8), bootup(7)

systemd 252

SYSTEMD-HALT.SERVICE(8)