



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'tipc-nametable.8' command

\$ man tipc-nametable.8

TIPC-NAMETABLE(8)

Linux

TIPC-NAMETABLE(8)

NAME

tipc-nametable - show TIPC nametable

SYNOPSIS

tipc nametable show

OPTIONS

Options (flags) that can be passed anywhere in the command chain.

-h, --help

-j, -json

Output results in JavaScript Object Notation (JSON).

-p, -pretty

The default JSON format is compact and more efficient to parse.

but hard for most users to read. This flag adds indentation for

readability.

Show help about last valid command. For example `tipc nametable`

--help will show nametable help and tipc --help will show gen?

er help. The position of the option in the string is irrele?

vant

DESCRIPTION

The nametable shows TIPC publication information.

Nametable format

Type

The 32-bit type field of the port name. The type field often indicates the port's function.

dicates the class of service provided by a port.

Lower

The lower bound of the 32-bit instance field of the port name.

The instance field is often used as a sub-class indicator.

Upper

The upper bound of the 32-bit instance field of the port name.

The instance field is often used as a sub-class indicator. A difference in lower and upper means the socket is bound to the port name range [lower,upper]

Port Identity

The unique socket (port) identifier within the TIPC cluster. The port identity consists of a node identity followed by a socket reference number.

Publication

The publication ID is a random number used internally to represent a publication.

Scope

The publication scope specifies the visibility of a bound port name. The scope can be specified to comprise three different domains: node, cluster and zone. Applications residing within the specified scope can see and access the port using the displayed port name.

EXIT STATUS

Exit status is 0 if command was successful or a positive integer upon failure.

SEE ALSO

[tipc\(8\)](#), [tipc-bearer\(8\)](#), [tipc-link\(8\)](#), [tipc-media\(8\)](#), [tipc-node\(8\)](#),
[tipc-peer\(8\)](#), [tipc-socket\(8\)](#)

REPORTING BUGS

Report any bugs to the Network Developers mailing list <netdev@vger.kernel.org> where the development and maintenance is primarily done. You do not have to be subscribed to the list to send a message there.

AUTHOR

Richard Alpe <richard.alpe@ericsson.com>

iproute2

02 Jun 2015

TIPC-NAMETABLE(8)