



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'tracker-xdg-portal-3.1' command

\$ man tracker-xdg-portal-3.1

TRACKER-XDG-PORTAL(1) Tracker manual TRACKER-XDG-PORTAL(1)

NAME

tracker-xdg-portal-3 - Portal to Tracker endpoints

SYNOPSIS

tracker-xdg-portal-3 [--version | -v]

DESCRIPTION

This daemon allows access to Tracker endpoints in a controlled manner.

By default access to every service is disallowed, services may be whitelisted through additional policy in the .flatpak-info file.

When whitelisting services, the policy may define specific graph names to allow access to, the default keyword to allow access to the default unnamed graph, or * keyword to allow access to all graphs.

CONFIGURATION

When interacting with sandboxed clients, the service expects the following format in the .flatpak-info file:

[Policy Tracker3]

dbus:org.example.SparqlEndpoint1=graphA;graphB;default

dbus:org.example.SparqlEndpoint2=*

This will allow access to the endpoints behind the org.example.SparqlEndpoint1 and org.example.SparqlEndpoint2 bus names.

Only to the graphA and graphB graph IRIs and the default unnamed graph on the first endpoint, and to all graphs in the second.

This policy can be set when building or running the sandboxed

application through the --add-policy option. This can be set via
finish-args in the flatpak manifest, specified along the build chain in
flatpak-build-finish(1), or modified at start time with flatpak-run(1).

For example:

```
$ flatpak run \  
  --add-policy=Tracker3.dbus:org.example.SparqlEndpoint1=graphA;graphB;default \  
  --add-policy=Tracker3.dbus:org.example.SparqlEndpoint2=* \  
  org.freedesktop.TrackerSandbox
```

SEE ALSO

[flatpak-build-finish\(1\)](#), [flatpak-override\(1\)](#), [flatpak-run\(1\)](#)

3.1.2

11/22/2022

[TRACKER-XDG-PORTAL\(1\)](#)