



## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'tuned.8' command***

***\$ man tuned.8***

tuned(8)                      Adaptive system tuning daemon                      tuned(8)

### **NAME**

Tuned - dynamic adaptive system tuning daemon

### **SYNOPSIS**

tuned [options]

### **DESCRIPTION**

tuned is a dynamic adaptive system tuning daemon that tunes system settings dynamically depending on usage.

### **OPTIONS**

-d, --daemon

This options starts tuned as a daemon as opposed to in the foreground without forking at startup.

-D, --debug Sets the highest logging level. This could be very useful when having trouble with tuned.

-h, --help Show this help.

-l [LOG], --log[=LOG]

Log to the file LOG. If no LOG file is specified  
/var/log/tuned/tuned.log is used.

--no-dbus Do not attach to DBus.

-P [PID], --pid[=PID]

Write process ID to the PID file. If no PID file is specified /run/tuned/tuned.pid is used.

-p PROFILE, --profile PROFILE

Tuning profile to be activated. It will override other settings (e.g. from tuned-adm). This is intended for debugging purposes.

-v, --version

Show version information.

## FILES

/etc/tuned

## SEE ALSO

tuned.conf(5) tuned-adm(8)

## AUTHOR

Jan Kaluža <jkaluza@redhat.com>

Jan Vrálek <jvcelak@redhat.com>

Jaroslav Škarvada <jskarvad@redhat.com>

Phil Knirsch <pknirsch@redhat.com>

## REPORTING BUGS

Report bugs to <https://bugzilla.redhat.com/>.