



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'undocumented.3' command

\$ man undocumented.3

UNDOCUMENTED(3) Linux Programmer's Manual UNDOCUMENTED(3)

NAME

undocumented - undocumented library functions

SYNOPSIS

Undocumented library functions

DESCRIPTION

This man page mentions those library functions which are implemented in the standard libraries but not yet documented in man pages.

Solicitation

If you have information about these functions, please look in the source code, write a man page (using a style similar to that of the other Linux section 3 man pages), and send it to mtk.manpages@gmail.com for inclusion in the next man page release.

The list

authdes_create(3), authdes_getucrcd(3), authdes_pk_create(3), clntu?
nix_create(3), creat64(3), dn_skipname(3), fcrypt(3), fp_nquery(3),
fp_query(3), fp_resstat(3), freading(3), freopen64(3), fseeko64(3),
ftello64(3), ftw64(3), fwscanf(3), get_avphys_pages(3), getdiren?
tries64(3), getmsg(3), getnetname(3), get_phys_pages(3), getpub?
lickey(3), getsecretkey(3), h_errlist(3), host2netname(3), hostal?
ias(3), inet_nsap_addr(3), inet_nsap_ntoa(3), init_des(3),
libc_nls_init(3), mstats(3), netname2host(3), netname2user(3),
nlist(3), obstack_free(3), parse_printf_format(3), p_cdname(3),

p_cdname(3), p_class(3), p_fqname(3), p_option(3), p_query(3),
 printf_size(3), printf_size_info(3), p_rr(3), p_time(3), p_type(3),
 putlong(3), putshort(3), re_compile_fastmap(3), re_compile_pattern(3),
 register_printf_function(3), re_match(3), re_match_2(3),
 re_rx_search(3), re_search(3), re_search_2(3), re_set_registers(3),
 re_set_syntax(3), res_send_setqhook(3), res_send_setrhook(3), ruser?
 pass(3), setfileno(3), sethostfile(3), svc_exit(3), svcudp_enable?
 cache(3), tell(3), tr_break(3), tzsetwall(3), ufc_dofinalperm(3),
 ufc_doit(3), user2netname(3), wcschrnul(3), wcsftime(3), wscanf(3),
 xdr_authdes_cred(3), xdr_authdes_verf(3), xdr_cryptkeyarg(3), xdr_cryp?
 tkeyres(3), xdr_datum(3), xdr_des_block(3), xdr_domainname(3), xdr_get?
 credres(3), xdr_keybuf(3), xdr_keystatus(3), xdr_mapname(3), xdr_net?
 namestr(3), xdr_netobj(3), xdr_passwd(3), xdr_peername(3), xdr_rmt?
 call_args(3), xdr_rmtcallres(3), xdr_unixcred(3), xdr_yp_buf(3),
 xdr_yp_inaddr(3), xdr_ypbind_binding(3), xdr_ypbind_resp(3), xdr_yp?
 bind_resptype(3), xdr_ypbind_setdom(3), xdr_ypdelete_args(3),
 xdr_ypmaplist(3), xdr_ypmaplist_str(3), xdr_yppasswd(3),
 xdr_ypreq_key(3), xdr_ypreq_nokey(3), xdr_ypresp_all(3),
 xdr_ypresp_all_seq(3), xdr_ypresp_key_val(3), xdr_ypresp_maplist(3),
 xdr_ypresp_master(3), xdr_ypresp_order(3), xdr_ypresp_val(3), xdr_yp?
 stat(3), xdr_ypupdate_args(3), yp_all(3), yp_bind(3), yperr_string(3),
 yp_first(3), yp_get_default_domain(3), yp_maplist(3), yp_master(3),
 yp_match(3), yp_next(3), yp_order(3), ypprot_err(3), yp_unbind(3),
 yp_update(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A
 description of the project, information about reporting bugs, and the
 latest version of this page, can be found at
<https://www.kernel.org/doc/man-pages/>.