



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'wcstoumax.3' command

\$ man wcstoumax.3

WCSTOIMAX(3) Linux Programmer's Manual WCSTOIMAX(3)

NAME

wcstoimax, wcstoumax - convert wide-character string to integer

SYNOPSIS

```
#include <stddef.h>

#include <inttypes.h>

intmax_t wcstoimax(const wchar_t *nptr, wchar_t **endptr, int base);

uintmax_t wcstoumax(const wchar_t *nptr, wchar_t **endptr, int base);
```

DESCRIPTION

These functions are just like `wcstol(3)` and `wcstoul(3)`, except that they return a value of type `intmax_t` and `uintmax_t`, respectively.

ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

??

?Interface ? Attribute ? Value ?

??

?wcstoimax(), wcstoumax() ? Thread safety ? MT-Safe locale ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

`imaxabs(3)`, `imaxdiv(3)`, `strtoimax(3)`, `strtoumax(3)`, `wcstol(3)`, `wc?`

stoul(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2015-08-08

WCSTOIMAX(3)