



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'wmemchr.3' command

\$ man wmemchr.3

WMEMCHR(3) Linux Programmer's Manual WMEMCHR(3)

NAME _____

wmemchr - search a wide character in a wide-character array

SYNOPSIS

```
#include <wchar.h>

wchar_t *wmemchr(const wchar_t *s, wchar_t c, size_t n)
```

DESCRIPTION

The `wmemchr()` function is the wide-character equivalent of the `memchr(3)` function. It searches the `n` wide characters starting at `s` for the first occurrence of the wide character `c`.

RETURN VALUE

The `wmemchr()` function returns a pointer to the first occurrence of `c` among the `n` wide characters starting at `s`, or `NULL` if `c` does not occur among these.

ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7)

3Interface 3 Attribute 3 Value 3

3wmemchr() 3 Thread safety 3 MT_Safe 3

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

memchr(3), wcschr(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

WMEMCHR(3)